

MONITORING URBAN STREAMS: STRATEGIES AND PROTOCOLS FOR HUMID-REGION LOWLAND SYSTEMS

JENNA G. SCHOLZ^{1,2} and DEREK B. BOOTH¹

¹ *Center for Urban Water Resources Management, University of Washington, Seattle, Washington, U.S.A.*

² *Center for Streamside Studies, University of Washington, Seattle, Washington, U.S.A.
(E-mail: jscholz@u.washington.edu and dbooth@u.washington.edu)*

(Received 7 December 1999; accepted 22 May 2000)

Abstract. Governmental mandates and public awareness have forced progressively smaller and less sophisticated agencies and organizations to initiate stream monitoring programs, particularly in urban and urbanizing areas. Yet many of these monitoring efforts lack either a coherent conceptual framework or appropriately chosen methods, and they rely on monitoring techniques that are simply infeasible for these institutional settings. We propose a monitoring strategy, and specific existing monitoring protocols, that will be useful for the management and rehabilitation of streams in urbanizing watersheds. A monitoring strategy must be developed by 1) identifying the management question(s) being addressed, 2) determining the institutional level of effort required (and available) to effectively make particular kinds of measurements, and 3) identifying what specific parameters should and can be measured. Only a limited set of parameters show much utility or feasibility in addressing the most common management questions being faced by municipalities in urbanizing, humid-area regions of the United States. These include measures of riparian canopy, bank erosion and bank hardening, and in-stream large woody debris. With some additional expertise useful data can also be included on channel gradient, substrate composition, and pools. Nearly all of the other myriad parameters that have been measured historically on rivers and streams show little apparent value in these watershed and institutional settings.

Keywords: aquatic ecosystems, monitoring, streams, urbanization

1. Background

Monitoring of stream systems has moved from a rarefied, academic pursuit to an activity required of progressively smaller and less sophisticated government agencies and non-governmental organizations that lack technical expertise and experience. These efforts are commonly being implemented as a consequence of legislative mandates, from the state or Federal level, or as a condition of construction permits. Public agencies and citizen groups are thus actively measuring a variety of stream parameters, either to evaluate the environmental conditions or 'health' of these systems or to track changes in those conditions over time. Yet many of these monitoring efforts lack either a coherent conceptual framework or appropriately chosen methods, and, as such, do not produce adequate information to reach their intended goals. Furthermore, monitoring techniques developed in



research settings or by large Federal agencies are simply not feasible for the vast majority of municipalities that are now initiating these programs. As a result, an unprecedented opportunity to record and to analyze the effects of land-use changes on aquatic ecosystems, driven by rapid urbanization and growing public awareness of downstream consequences, is being lost.

Our intent here is to articulate a strategy for urban stream monitoring that acknowledges not only the geomorphic and hydrologic characteristics of the fluvial system, but also the typical range of institutional needs and constraints under which that monitoring is likely to occur. It is not sufficient for a monitoring plan to identify only parameters that can characterize the condition of a system; it must also ensure that the data can be collected feasibly and reproducibly within the institutional setting that the monitoring will occur. The assessment here is based on the current monitoring theory and practice in lowland watersheds of western Washington State (U.S.A.), where recent listings of anadromous salmon under the federal Endangered Species Act directly affect management of stream channels that are also being affected by the region's rapid urban growth. These watersheds have become the primary focus of monitoring by local municipalities and citizen volunteer groups, because many contain fish-bearing streams that are undergoing rapid and readily visible degradation. They range in drainage area from about 1–100 km², supporting perennial streams with typical bankfull widths of about 1–10 m on channel gradients of 10% for headwater systems down to about 0.5% for the mainstem channels.

Although substantial resources are being directed towards ecosystem monitoring, neither funding agencies nor implementing agencies have received much guidance in designing an appropriate monitoring program. The problem is not with executing specific monitoring protocols – many guidance documents exist that specify proper techniques for data collection, and so these issues are mentioned here only briefly. Instead, the major shortcoming is in choosing an *approach* that will provide sufficient data to answer particular management questions and that is feasible for the institutional context and available resources. The approach articulated here does not, and should not, lead to the same monitoring program for every stream in every institutional setting. It can, however, provide the basis for crafting the most appropriate monitoring programs across a variety of settings. It also leads to a set of 'typical' monitoring activities that should prove useful in many applications that have become commonplace in urbanizing regions of the United States.

Our goal is to identify a monitoring strategy, and specific existing monitoring protocols, that will be useful for the management and rehabilitation of streams in urbanizing watersheds. We have subdivided this goal into several tasks, discussed in the sections that follow:

1. Establish the monitoring strategy. This consists of:
 - articulating what management question(s), commonly generated by gov-

- ernment agencies, a variety of other stakeholders, or regulatory mandates, are being addresses by the monitoring;
- determining the level of effort required to make particular kinds of measurements effectively; and
 - identifying what to measure.
2. Evaluate the utility of individual monitoring parameters currently being used to characterize particular features of the channel, as measures of stream condition.
 3. Recommend a set of stream-monitoring protocols that will meet the most common needs of agency monitoring programs in urban and urbanizing areas.

2. Monitoring Strategy

2.1. ARTICULATING MANAGEMENT QUESTIONS

We recognize three common questions that depend on characterizing the condition of streams in urbanizing watersheds:

- (1) What are the trends in stream condition?
- (2) What is the current stream condition?
- (3) How should planned stream restoration or rehabilitation efforts be ranked?

Although related, these questions require different types of measurements at different levels of detail and precision. The first is the simplest to answer, because it requires only a set of measurements that show a response to watershed changes, repeated at the same location over time. The measurements need not be transferable, only reproducible.

In contrast, the second question (and commonly the third) carries an implicit or explicit comparison to some reference condition that is presumed to be 'good'. This requires not only that the measurements be accurate and transferable from one stream to another, but also that the chosen reference is truly applicable. Accordingly, some method of stream stratification or classification is required in order to select appropriate comparisons from the tremendous variety of natural stream types. Any monitoring with this goal requires such a framework, either implicitly stated – criteria for a 'good' boulder-strewn cascade, for example, will be dramatically different than for a languid lowland creek.

The third question for monitoring, how to rank prospective rehabilitation efforts, adds additional dimensions – how bad are conditions now? How good might they become? What elements of a healthy stream are most degraded? Can they be repaired? This demands the most comprehensive view of the channel, because streams can be degraded in many different ways. Although we find some similarities among many urban channels, no single strategy for rehabilitation will be effective in every case. Accordingly, part of the task for a monitoring program is

to gather data that will help identify the most likely approach for success, and to provide scientifically based justification for any chosen course of action.

2.2. LEVEL OF MONITORING EFFORT

Many monitoring programs include unrealistically complex protocols for the level of staff or volunteers available. To provide a basis for comparison, we have used the following scale of institutional 'levels of effort':

- (1) Rapid, low cost, but likely to generate only qualitative or imprecise quantitative data. Level 1 measures are single snapshot evaluations and typically have modest utility because they can reliably offer only a coarse discrimination of aquatic-system condition. However, they may be useful in evaluating gross condition ('good' vs. 'bad'), and they are suitable for a wide range of volunteers with only minimal training.
- (2) Nominal equipment, relatively rapid, and likely to generate reproducible (albeit coarse) quantitative results. These techniques require trained volunteers that are familiar with field and laboratory procedures and practices. At this level of effort, measures can be useful to classify a stream or reach, or to characterize relative to some reference condition. As such, they can be used for both one-time and continuous monitoring programs; however, most parameters are not precisely measured or discriminated, and so they will require substantial change for any difference to be detected.
- (3) Similar requirements and applications as Level 2 but requiring more time and more specialized training in order to yield more precise results; discrimination of trends should be commensurately improved.

2.3. WHAT TO MEASURE

Finally, effective monitoring requires knowledge of *what* to measure. This analysis addresses only selected *physical* elements of the stream system, in explicit contrast to the historic regulatory-driven emphasis on chemical parameters and the growing attention to in-stream biota (Karr, 1998). We have chosen this emphasis for several reasons:

- In a majority of settings, the most rapid and severe stream degradation is a consequence of physical effects, particularly high flows and riparian alteration, not chemical contamination (Horner *et al.*, 1997). For most (but not all) monitoring assessments, collecting a statistically meaningful set of chemical data is simply not worth the substantial effort needed.
- Recent articulation and application of biological monitoring techniques are readily available elsewhere (e.g. Fore *et al.*, 1996; Karr and Chu, 1999).
- Unlike most chemical and biological evaluations, physical measurements are relatively quick and easy to make and inexpensive to analyze; most can be

accomplished during any time of the year and at all but the highest of stream discharges. They can also provide specific information on potential causes of stream degradation, and so help guide rehabilitation efforts where improvement of biological conditions is the desired outcome.

We recognize six *channel features* of particular importance, based on a growing understanding of how lowland channels respond to urbanization (Hollis, 1975; Dunne and Leopold, 1978; Booth, 1991; Horner *et al.*, 1997; Booth and Jackson, 1997):

1. channel geometry,
2. stream corridor vegetation,
3. channel erosion and bank stability,
4. large woody debris,
5. channel-bed sediment, and
6. instream physical habitat.

Where comparison of these channel features to a reference condition is required by the management question(s), they need to be grouped into consistent channel types. Without such grouping, comparison of between-group variability is meaningless. We recommend the geomorphologically based approach of Montgomery and Buffington (1997), developed for forested mountain drainage basins in the Pacific Northwest, because it displays a clear relationship between channel 'type' and channel behavior that is often lacking in more purely descriptive approaches (e.g. Rosgen, 1994). They define a range of stream types, of which four are particularly relevant to a humid-region, lowland setting.

Of the alluvial channels encountered in lowland watersheds and their headwater tributaries, *cascade channels* are the steepest, characterized by large clasts that form the primary roughness elements and impose a strongly three-dimensional structure to the flow. Tumbling flow around individual boulders dissipates most of the energy of the flow; bed morphology is disorganized with at most small pools that span a fraction of the total channel width. *Step-pool channels*, in contrast, display full-width-spanning accumulations of coarse sediment that form a sequence of steps, typically one to four channel-widths apart, that separate low-gradient pools filled with finer sediment. The step-forming sediment can be mobilized but only at very high discharges. *Plane-bed channels* lack well-defined bedforms and instead display long, and commonly channel-wide, reaches of uniform 'riffles' or 'glides'. In contrast to the steeper channels any flow oscillation is generally horizontal, not vertical, but the lateral variations are insufficient to produce pronounced meander and associated pools. The most common of the lowland stream channels, *pool-riffle channels*, have laterally oscillating flow that produces a sequence of pools at the outside of bends with corresponding bars on the inside of bends. The classification discriminates between 'free' pool-riffle channels, where this distinctive morpho-

logy forms simply by virtue of the inertial characteristics of the water moving in a sinuous or meandering channel; and 'forced' pool-ruffle channels, where the presence of pools is closely tied to obstructions such as large woody debris.

Outlining an overall strategy, articulating questions, determining the available level of effort, and identifying what to measure are the first tasks of a successful monitoring effort. Typically, most of the time and resources in a monitoring program are invested in the task that follows, the selection and measurement of specific parameters. This relative emphasis, however, should not obscure the importance of first establishing the strategy, as it guides all subsequent tasks.

3. Channel Features and Monitoring Parameters

3.1. CHANNEL GEOMETRY

Channel geometry describes the physical structure of a stream channel. Several different elements are included here, and a variety of parameters are currently used to measure this channel feature (Table I).

The most useful measure of channel geometry is bankfull channel dimension, such as given by cross-section measurements, and in particular the bankfull width. There are several reasons for this:

- Bankfull width and depth measurements can be measured quickly and require limited equipment. These measures are the primary variables for relating channel size to watershed parameters such as area, flood frequency, or level of development. However, experience is necessary to identify bankfull height consistently because a variety of indicators are needed to identify it reliably (Williams, 1978), and some uncertainty in reported bankfull channel dimensions is almost inescapable (Johnson and Heil, 1996).
- Documented channel changes can be very useful in trends analysis. For example, cross section data can be used to identify changes in channel geomorphology over time (Leopold, 1973; Booth, 1997; Booth and Henshaw, 2000) with almost no risk of subjective misinterpretation. Bankfull channel dimensions can be measured more rapidly than full cross sections, but documenting changes in bankfull channel dimensions require a greater magnitude of channel change than for cross sections.
- With an adequate regional compilation of channel dimensions, these measurements can show the relative deviation of channel geometry from anticipated undisturbed conditions (Dunne and Leopold, 1978; Booth and Jackson, 1997). They can therefore help evaluate current conditions and prioritize streams for rehabilitation.
- Several other measures of channel geometry, particularly gradient and valley confinement, do not discriminate 'good' from 'degraded' channels and are

TABLE I
Parameters used to assess channel geometry

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Wetted width	Measured at specified distances	1	L	L	L
Cross sections	Monumented survey of cross-channel profile	2	H	L	L
Gradient	Various methods using different instruments for different degrees of precision	2 or 3	L	H	H
Bankfull width and depth	Determined using visual observations and/or channel profiles; taken at specified distances	3	M	M	H
'Flood-prone width' or valley confinement	determined using visual observations or defined as the flow width at a specified multiple (usually 2 ×) of the bankfull depth	3	L	L	H

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

The management applications ('Trends', 'Current Health', and 'Ranking') correspond to the three questions posed earlier: (1) What are the trends in stream condition? (2) What is the current stream health? (3) How should planned stream restoration or rehabilitation efforts be ranked?

unlikely to change significantly over time. They are not useful, therefore, for one-time evaluations or for trend analyses, but they provide necessary information for the design of rehabilitation projects. As such they are relevant to one of our three management questions, even though they may not be part of the 'monitoring' effort itself.

By comparison, some other common measurements are not as effective in characterizing the physical dimensions of the channel. For example, measurements of the wetted width vary with rising and falling stage, and this parameter may change by a factor of two or more in the course of a single day. Thus although useful for certain fisheries applications, it is not reliable for trend analysis and does not provide information needed to prioritize restoration projects.

3.2. STREAM CORRIDOR VEGETATION

Stream corridor vegetation describes the amount of area above and adjacent to the stream (the riparian corridor) occupied by vegetation (Table II).

TABLE II
Parameters used to assess corridor vegetation

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Canopy	Numerical rankings (e.g., 'low', 'medium', and 'high'); observer judgment	1	L	M	H
Shade percentage	Gridded mirror (densiometer) used to measure percent shade	2	H	H	H
Ground cover	Three verbal rankings of 'low', 'medium' or 'high'; observer judgment	2	L	L	L
Shrub layer	Three verbal rankings of 'low', 'medium' or 'high'; observer judgment	2	L	M	L

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

Numerous studies have demonstrated a close correlation between intact corridor and good instream conditions (e.g. Steedman, 1988; May, 1996; Horner *et al.*, 1997) in both agricultural and urbanizing environments, and so this feature has particularly high utility. Shade percentage and canopy measurements collected using a spherical densiometer have greater precision and replicability than unaided visual estimates because they provide a calibrated means of measuring vegetation within the stream corridor. For this reason, use of this instrument is standard in forest practices (Lemmon, 1957). Characterization of riparian vegetation using this parameter can be readily used to accurately describe both current conditions and long-term trends within the stream corridor. However, use of a densiometer does require some training and may be unnecessarily time consuming for some applications (such as those where the majority of riparian shade has already been removed through management activities).

Canopy estimates made using several percentage classes (e.g. 0–25, 25–50%, etc.) are adequate for many applications. These measurements can be performed readily in the field with fair replicability and limited training. However, unaided estimates of percent canopy are prone to some observer error and are less precise than measurements made with a densiometer, and so they will not be nearly as sensitive to changes over time.

3.3. CHANNEL EROSION AND BANK STABILITY

Channel erosion and bank stability describe the conditions of the stream bank by characterizing the amount of bank erosion present and the relative stability of the

TABLE III
Parameters used to assess bank erosion and bank stability

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Bank erosion	Photographic record of the erosion and estimated location on map	1	M	M	H
	Presence/absence by map location or by reach; observer judgment	1	L	M	M
	Verbal rankings for magnitude of bank erosion, located by reach	2	M	H	H
	Distance from beginning of habitat unit to location of erosion; left/right of channel. Letter codes for type of slope failure, determined from comparison with pictures and written descriptions; observer judgment.	3	M	H	H
Bank hardening	Description or photographic record; location by reach or plotted on map	2	M	M	M

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

bank. Measuring bank erosion, particularly in urban areas, is a critical parameter for assessing channel condition and for guiding rehabilitation, because it is one of the few ways available to recognize the hydrologic disturbance that typically accompanies urban development (Hollis, 1975; Booth, 1991) (Table III).

We recommend using methods of verbal ranking, with or without a photographic record, as this information requires minimal effort, generally describes current conditions, is useful for some level of trend analysis, and can locate areas for habitat restoration. Established channel-assessment methods typically divide the observed range of bank (in)stability into several distinct categories of descriptive conditions, which appears to be a useful and replicable degree of detail. Henshaw (1999) has developed a descriptive characterization based in part on Galli (1996a, b) with particularly good applicability and tested replicability (Table IV).

In contrast, more laborious measurements of bank erosion are rarely of much use. For example, identifying the length and location of an erosional zone and plotting it on a map can increase the precision of the original measurements but requires substantially more training and more field time. The utility of such measurements is uncertain – unless the purpose is to identify specific sites for bank repair, such

TABLE IV
Streambank stability classification criteria (from Henshaw, 1999)

Class	Description
4	<p>Stable</p> <ul style="list-style-type: none"> • perennial vegetation to waterline • no raw or undercut banks (some erosion on outside of meander bends OK) • no recently exposed roots • no recent tree falls
3	<p>Slightly unstable</p> <ul style="list-style-type: none"> • perennial vegetation to waterline in most places • some scalloping of banks • minor erosion and/or bank undercutting • recently exposed tree roots rare but present
2	<p>Moderately unstable</p> <ul style="list-style-type: none"> • perennial vegetation to waterline sparse (mainly scoured or stripped by lateral erosion) • bank held by hard points (trees, boulders) and eroded back elsewhere • extensive erosion and bank undercutting • recently exposed tree roots and fine root hairs common
1	<p>Completely unstable</p> <ul style="list-style-type: none"> • no perennial vegetation at waterline • banks held only by hard points • severe erosion of both banks • recently exposed tree roots common • tree falls and/or severely undercut trees common

data are commonly used simply to indicate those reaches, in aggregate, that display a relatively high degree of erosion. If the specific sites themselves will never be resurveyed, the detailed description of their location or character will not be used for either current assessment or subsequent remediation.

3.4. LARGE WOODY DEBRIS

Large woody debris (LWD) is used as a general indicator of watershed condition in forested (and once-forested) watersheds. Low levels of LWD can result in a reduced number of pools, pool quality, gravel and organic debris levels, and habitat complexity (Bisson *et al.*, 1987; Grette, 1985; Harris, 1987; Bilby and Bisson, 1992). Good correlation has been demonstrated between the degree of watershed

TABLE V
Parameters used to assess large woody debris (LWD)

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Large woody debris (LWD)	Tally per length of stream reach	1	H	H	H
	Four numerical zones used to identify the location within the stream channel	2	H	H	H
	Distance from the beginning of the stream habitat unit to the location of the LWD	3	M	L	M
	Four numerical zones used to identify the stability of the LWD	3	H	H	H
	Pool forming	3	M	H	M
'Small' woody debris (SWD)	Tally per length of stream reach	2	L	M	L
LWD jams	Length, width, height, and number of individual wood pieces	3	M	M	M

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

urbanization and the number of instream LWD pieces in urbanizing Pacific Northwest channels (May, 1996; Horner *et al.*, 1997; Booth *et al.*, 1997). Parameters used by local agencies to measure woody debris include the length and diameter of the LWD, length and diameter of small woody debris (SWD), location and stability of logs, percentage of wood covering and creating pools, rootwad diameter, and dimensions of LWD jams (Table V).

The parameters and methods used to measure LWD generally provide useful information on current conditions, can be used in trend analyses, and are useful in prioritizing restoration projects. Similarly, all require some training to collect accurate field measurements. We recommend that specific minimum diameter and length criteria be used in counting LWD because they appear to improve accuracy and replicability while requiring little additional training. There are no absolute minimum size criteria for LWD, however; agencies contemplating cooperative data collection need to agree to a common standard. A minimum diameter of 25 cm (10 in) is a common criterion in the published literature. For example, Bilby and Ward (1989) do not report any stable LWD less than this size; Montgomery *et al.* (1995), citing Swanson *et al.* (1976), use this as their minimum diameter for LWD;

and Oregon Department of Forestry (1995) do not allow logs of lesser diameter for their rehabilitation projects.

The minimum *length* of LWD, however, has less agreement. Bilby (1984) suggests that any piece shorter than 5 m may be unstable; Bilby and Ward (1989) counted none shorter than 4.5 m in their study; Montgomery *et al.* (1995) counted any piece longer than 1 m; Oregon Department of Forestry (1995) requires a length double to that of the bankfull width. A minimum length of 3 m (10 ft), in combination with the minimum diameter criterium of 25 cm (10 in), is a defensible, appropriate, and easily remembered standard to use where none other has been agreed upon. However, restoration projects must consider stream size in determining the specific length and diameter of replacement LWD, and a monitoring program focusing on large rivers might elect to use different minimum size criteria than suggested here.

The remaining parameters sometimes used by agencies include length and diameter of 'small' woody debris, location and stability of logs, percentage of wood covering and creating pools, rootwood diameter, and dimensions of LWD jams. Measuring these parameters may be useful for specific fish-habitat assessments, but in general they are too detailed and require more training than is necessary to assess LWD in urbanizing watersheds.

3.5. CHANNEL-BED SEDIMENT

Although *channel-bed sediment* is critical to the physical and biological functioning of stream channels, most of the commonly measured parameters are not suitable for use in the type of monitoring program we are considering. In part, this is due to the difficulty in creating certain types of reliable, replicable data for this channel feature, and because there are few reliable correlations between channel-bed sediment and overall stream condition (Table VI).

The most common parameter (point counts of the substrate) is useful only if measurements are made in equivalent locations along a stream and between streams. Specifically, measurements should be made on upstream sides of point bars at low flow or in uniform channel-spanning riffles where no point bars are present (Reid and Dunne, 1996; Kondolf, 1997). Measuring this parameter therefore requires modest training. More importantly, *interpreting* the resulting data generally requires experience in sediment analysis that is beyond the scope of this evaluation. Variability in the channel gradient, source area, season of measurement, and history of recent high flows all can affect the measured values of this parameter without any corresponding influence from watershed disturbance. Suggestively, however, one study across a number of Puget Lowland streams showed a good correlation between substrate size and high-quality biological conditions (May, 1996).

Embeddedness can also be a useful monitoring parameter, because it can be measured with moderate precision and clearly affects certain elements of channel

TABLE VI
Parameters used to assess channel-bed sediment

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Substrate composition	Point and count method	2	M	M	L
	Six letter ranking codes for substrate size, based on single-particle estimation of diameter at ten equally-spaced points across the channel	2	L	L	L
Embeddedness	Numerical ranking from 1 to 5; visual estimation of percent sediment and cover of gravel, boulders, rubble	3	M	M	M
	Measure % fines in gravel	3	M	M	M
Type of substrate (average over bed area).	Type substrate (sand, silt, clay) based on visual estimation of particle size	2	L	L	L

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

condition, particularly the viability of benthic animals and incubating fish eggs. However, it does not provide an unambiguous characterization, because different streams can have very different sediment characteristics as a consequence of different gradient and source areas. Thus a snapshot characterization of embeddedness might show if a channel had a suitable substrate for biota but would *not* necessarily demonstrate that the cause of poor conditions was from human disturbance. MacDonald *et al.* (1991, p. 124) note that: 'Embeddedness has shown promise, but the immediate need for a monitoring technique has resulted in widespread use and adaptation before cobble embeddedness could be adequately field-tested and validated'. Change in this parameter over time may guide protection or rehabilitation strategies, although Burns and Reis (1989) judged that five consecutive years of embeddedness data were necessary to evaluate trends in a mining district in Idaho. Galli (1996a, b) groups embeddedness fractions (% fines on the bed surface) into four categories (0–25, 25–50%, etc.) but does not report the sensitivity of these groupings to changes in the channel or the watershed. Observations suggest that channels can fully span the range from 1 to 100% embeddedness and that the differences are well correlated both with human disturbance of the watershed and with biological utilization of the stream channel (May, 1996; Wydzga, 1997). However,

we have no data on the rate at which such changes can occur and thus no basis to judge the predictive value of this parameter.

Other sediment parameters yield data with limited application in assessing urbanizing watersheds for a variety of reasons:

- Sediments sizes vary markedly between different morphologic units (e.g. between pools and riffles). Characterization of the substrate without reference of the morphology of the channel will not provide replicable or comparable data, and so it will not be useable for establishing conditions or trends. If such data are needed, the point-counting method of Wolman (1954) is well established and is relatively quick and easy. Kondolf (1997) emphasizes that the various alternative methods of sampling, such as single-grain measurements or 'zig-zag' sampling across and down a reach of channel (Bevenger and King, 1995) yield non-reproducible results with little or no predictive value.
- Use of visual substrate classifications is an unnecessary loss of accuracy (Chapman and McLeod, 1987; MacDonald *et al.*, 1991). For surface-sediment sampling, the pebble-count method of Wolman (1954) has good statistical replicability for only a modest expenditure of additional time.
- More detailed characterization of 'substrate' requires not only the measurement of the surface sediment but also, for gravel-bedded channels, that of the sediment below the upper layer of (usually coarser) gravel. Such subsurface measurements are even more time-consuming, although with care they are useful in characterizing habitat suitability given the overall size distribution of the gravel and the percentage of void-filling fine sediment. The techniques available to make such measurements (Platts *et al.*, 1983; Church *et al.*, 1987) are beyond the scope of this evaluation. However, C. P. Konrad (1999, pers. comm.) found a strong correlation between the surface-sediment D_{10} (i.e. the finest 10th percentile), the median substrate grain size, and biological condition in Puget Lowland streams.

4. Instream Physical Habitat – Pools, Riffles, and other Habitat Units

Characterizing *instream physical habitat* has a long history in undisturbed, forested watersheds. This approach is intuitively well founded – if one of our primary interests is the ability of the channel to support organisms, what better way to assess that 'ability' than to measure the features of the channel directly associated with biological use?

Two factors limit the utility of direct measures of channel habitat features. Although researchers and field personal have articulated these limitations for over a decade, the consequences of those limitations have not been consistently reflected in many monitoring programs:

1. The measurement or characterization of such features is imprecise and subject to substantial observer error. This is true of nearly all monitoring parameters: however, the magnitude of typical errors associated with habitat-unit inventories renders data inappropriate for between-stream or time-trend comparisons.
2. In-channel physical habitat features do not necessarily respond rapidly to human disturbance, and so even if a measurable change in such a monitoring parameter can be documented it may come far too late, if at all, to trigger an effective management response.

Both of these limitations are the subject of an extensive, recent literature review and analysis (Poole *et al.*, 1997). Their conclusion is particularly germane to our current evaluation:

'Habitat-unit classification was not designed to quantify or monitor aquatic habitat. At the level necessary for use as a stream habitat monitoring tool, the method is not precise, suffers from poor repeatability, cannot be precisely described or accurately transferred among investigators, can be insensitive to important human land-use activities, is affected by stream characteristics that vary naturally and frequently, and is not based on direct, quantitative measurements of the physical characteristics of interest. Relying on habitat-unit classification as a basis for time-trend monitoring is time-consuming, expensive, and ill-advised'. (Poole *et al.*, 1997, p. 894)

They base their conclusions in part on the work of four studies that specifically investigated observer bias (Platts *et al.*, 1983; Hankin and Reeves, 1988; Ralph *et al.*, 1991; Roper and Scarnecchia, 1995). For example, Roper and Scarnecchia (1995) found that five days of standardized training were *insufficient* to produce consistent results among different observers when a full range of habitat units (nine, in their study) was used. Even if high precision could be achieved, a variety of researchers have noted the relative insensitivity of habitat units to land-use changes or other human impacts (Warren *et al.*, 1987; MacDonald *et al.*, 1991; Ralph *et al.*, 1994). We therefore anticipate that most such efforts will combine the unfortunate attributes of large time commitments, non-repeatable results, and limited predictive or management utility.

Despite the generally poor record for habitat assessment in monitoring programs, we recognize the underlying conceptual basis for including some aspect of these channel features among the list of monitoring parameters. Useful results are most likely where the number of habitat categories is small. Roper and Scarnecchia (1995) reported complete agreement among their multiple observers for only 25% of the classified units, using their full set of nine categories. In contrast, their observers achieved a more useful 75% agreement when only three units were being discriminated (pools, riffles, and glides). We recommend focusing on *pools*, because they show a crude but consistently inverse correlation with human watershed

TABLE VII
Evaluation of parameters used to assess pools

Parameter	Method of measurement	Level of effort	Trends	Current health	Ranking
Tally of 'large' pools in reach	Identified using size criteria for residual depth and wetted channel width	2	L	H	M
Maximum depth	Deepest point in the pool	2	L	M	L
Principal cause of pool formation	Numerical ranking from 1 to 11, based on what is blocking the stream flow	3	L	L	L
Pool types	Pool types identified by comparison with written description; observer judgment	3	L	L	L

L = not useful for the identified management question at the specified level of effort; M = moderately useful; H = very useful.

disturbance across a wide range of landscape types (e.g. Booth, 1990; Peterson *et al.*, 1992; Galli, 1996a; May, 1996) (Table VII).

We recommend measuring pool width and depth over any alternative parameters because they provide adequate assessment of current conditions and require only moderate training. In addition, these measurements can be quickly collected and they require little field equipment (see also Robinson and Kaufman, 1994).

However, substantial observed variability, seasonal variability in flow, and variability caused by instream objects such as boulders or LWD (MacDonald *et al.*, 1991; Myers and Swanson, 1997; Poole *et al.*, 1997) make measuring and interpreting pool habitat problematic. Accordingly, monitoring pools is often not useful for the specific tasks being evaluated in this report and so their overall value is moderate at best. If the intent of the monitoring is to render a one-time evaluation of stream condition, close attention to channel classification is also necessary, because the criteria for a 'good' number and dimension of pools change dramatically among the different channel types.

Habitat types other than pools do *not* appear to be suitable for use in the type of monitoring program we are considering. This is primarily because of the difficulty and expense in generating reliable, replicable data for these other habitat parameters, as much or more so than with pools. Information gathered during assessment of other channel features (e.g. channel geometry) can probably generate equivalent information with much greater reliability and greater insight into the *cause* of physical-habitat change (MacDonald *et al.*, 1991; Poole *et al.*, 1997).

TABLE VIII
Summary of recommended 'Level 1' measurements

Parameter	Method of measurement
Canopy	Visual estimate of canopy cover, expressed as a percentage range (e.g. 0–25%, 25–50%, 50–75%, 75–100%)
Bank erosion and bank hardening	Verbal rankings for magnitude of bank erosion, located by reach (and representative photographs if desired)
Large Woody Debris; minimum length >3 m (10') and minimum diameter >25 cm (10")	Tally of the number of pieces in the channel in a specified length or reach of stream

5. Recommended Monitoring for Urban Stream Systems

Although there is general agreement that the physical conditions of streams are important determinants of aquatic quality, there is little agreement on the best way to measure or to characterize those physical conditions. Even though many agencies and volunteer groups may be collecting voluminous amounts of stream-condition data, no region can comprehensively assess the status of its entire aquatic system. This problem is compounded in urban and urbanizing areas, because most of the monitoring protocols currently in use have been developed for other purposes or in other settings, notably the forested slopes of the adjacent mountains.

Based on this evaluation, we see a limited set of monitoring tasks appropriate to a rapid, low-cost effort ('Level 1' in the tables below), although the benefits of enhanced stewardship by involving volunteer monitoring far exceed any concerns about data imprecision at this level of effort. The measurements that are suggested by our analysis are given in Table VIII.

This is a much shorter list than even the lowest-effort monitoring plan typically includes, and we emphasize that there may be a number of reasons why an expanded list might be appropriate. If, however, the intended purpose is simply to provide useful information for guiding management decisions, we see little evidence that additional tasks executed as the lowest level of effort will produce any useable results. With these measurements, a coarse discrimination of stream quality is possible, and the worst channels – barren, raw channels with neither cover nor diversity – will be apparent. Detecting change over time, however, will be highly *insensitive*; damage will occur long before these methods can unequivocally identify it.

At a greater level of effort ('Level 2', requiring trained volunteers or professionals but minimal equipment and modest field time) the range of recommended tasks is greater and includes several of the activities that normally constitute many agen-

TABLE IX
Summary of recommended 'Levels 1 and 2' measurements

Parameter	Method of measurement
Gradient	Several alternative methods are available, with the use of hand-held equipment generally adequate
Shade/canopy	Gridded mirror (densiometer) used to measure the percent shade, or visual estimate of canopy cover
Bank erosion and bank hardening	Verbal rankings for magnitude of bank erosion, located by reach
Large Woody Debris; minimum length >3 m (10') and minimum diameter >25 cm (10")	Tally of the number of pieces in the channel in a specified length or reach of stream; include four numerical zones used to identify the location within the stream channel <i>or</i> limit tally to those pieces within bankfull channel
Substrate composition	'Point and count' method with 100 randomly selected grains from upstream side of point bar or channel-spanning riffle
Pools (specify minimum depth for inclusion)	Tally and measurement of the number of pools in a specified length or reach of stream, using residual depth and wetted channel width to define minimum size

cies' 'stream monitoring program' (Table IX). Level 2 measurements are useful because 1) they provide more a detailed and precise evaluation of stream quality than Level 1 measurements, 2) they offer the chance to detect modest changes in channel conditions over time, 3) they identify credible reference conditions, and 4) they generate some of the information needed to design a rehabilitation project. However, some commonly executed tasks are absent from this recommendation. Those omitted tasks either require an even greater level of effort in order to produce reliable results, or there is no evidence that *any* level of effort applied to them can achieve practical guidance for our three management questions in the urban environment.

6. Summary

We have evaluated the commonly used monitoring approaches and protocols for evaluating the physical condition of urban streams. Through this effort, we have found that the list of useful and feasible measurements is surprisingly short. The recommended parameters characterize, either directly or indirectly, many of the physical changes that befall urban streams. These include disrupted hydrology

(measured here through its consequences on scour and bank erosion), loss of riparian corridor (canopy measurements), and the combined influence of high flows and increased upstream scour on in-stream sedimentation and habitat diversity (parameters for measuring sediment, LWD, and pools). Because these changes are interrelated, no simple set of measurements will give unequivocal guidance of the *cause* of, and thus the most effective solution for these problems. However, appropriately selected measurements should help define the kinds of rehabilitation approaches that should address the most seriously degraded elements of the urban stream system. If the institutional reason for the monitoring, and the institutional constraints on its execution, are clearly articulated and acknowledged throughout the process, the monitoring effort should yield genuinely useful data.

Acknowledgements

We are indebted to the assistance we have received from our agency and academic colleagues, particularly Kate O'Laughlin of King Country Water and Land Resources Diversion, Kit Paulson at the City of Bellevue, Kathy Thornburgh of Snohomish County Surface Water Management Diversion, and Christopher May of the University of Washington. Support for this project was provided by the City of Bellevue, King County, the U.S. Environmental Protection Agency's Waters and Watersheds Program Grant No. R825284-01-0, and the Center for Urban Water Resources Management at the University of Washington. Initial study was supported by the Natural Resources Conservation Service, Watershed Science Institute.

References

- Bevenger, G. S. and King, R. M.: 1995, *A Pebble Count Procedure for Assessing Watershed Cumulative Effects*, Fort Collins, CO, U.S. Department of Agriculture, Forest Service Research Paper RM-RP-319, Rocky Mountain Forest and Range Experiment Station.
- Bilby, R. E.: 1984, 'Post-logging removal of woody debris affects stream channel stability', *J. of Forestry* **82**, 609-613.
- Bilby, R. E. and Bisson, P. A.: 1992, 'Allochthonous versus autochthonous organic-matter contributions to the trophic support of fish populations in clear-cut and old-growth forested streams', *Can. J. Fish. Aquat. Sci.* **49**(3), 540-551.
- Bilby, R. E. and Ward, J. W.: 1989, 'Changes in characteristics and function of woody debris with increasing size of streams in western Washington', *Trans. Amer. Fish. Soc.* **118**, 368-378.
- Bisson, P. A., Bilby, R. E., Bryant, M. D., Dolloff, C. A., Grette, G. B., House, R. A., Murphy, M. L., Kosku, K. V. and Sedell, J. R.: 1987, 'Large Woody Debris of Forested Streams in the Pacific Northwest: Past, Present and Future', in: E. O. Salo and T. W. Cundy (eds.), *Streamside Management: Forestry Fishery Interactions*, Contribution No. 57, Institute of Forest Resources, University of Washington, Seattle, WA, pp. 141-191.
- Booth, D. B.: 1990, 'Stream-channel incision following drainage-basin urbanization', *Water Res. Bull.* **26**, 407-417.

- Booth, D. B.: 1991, 'Urbanization and the natural drainage system – impacts, solutions and prognoses', *Northwest Environ. J.* **7**, 93–118.
- Booth, D. B.: 1997, 'Long-term measurement of channel changes in urban and suburban watersheds', *Eos*, American Geophysical Union, Fall Meeting, **78**, F313.
- Booth, D. B. and Henshaw, P. C.: 2000, 'Rates of Channel Erosion in Small Urban Streams', in: M. Wigmosta (ed.), *Stream Channels in Disturbed Environments*, AGU Monograph Series.
- Booth, D. B. and Jackson, C. J.: 1997, 'Urbanization of aquatic systems – degradation thresholds, stormwater detention, and the limits of mitigation', *Water Res. Bull.* **33**, 1077–1090.
- Booth, D. B., Montgomery, D. R. and Bethel, J.: 1997, 'Large Woody Debris in Urban Streams of the Pacific Northwest', in: L. E. Roesner (ed.), *Effects of Watershed Development and Management on Aquatic Ecosystems*, Engineering Foundation Conference, *Proceedings*, Snowbird, Utah, August 4–9, 1996, pp. 178–197.
- Burns, D. C. and Reis, R. D.: 1989, Embeddedness of salmonid habitat of selected streams on the Payette National Forest, 1987–1988, *Report to the Payette National Forest*, McCall, ID, 36 p.
- Chapman, D. W. and McLeod, K. P.: 1987, Development of criteria for fine sediment in the Northern Rockies ecoregion, Seattle, WA, *U.S. EPA, Water Division Report 910/9-87-162*, 279 p.
- Church, M. A., McLean, D. G. and Wolcott, J. F.: 1987, 'River Bed Gravel: Sampling and Analysis', in: Thorne *et al.* (eds.), *Sediment Transport in Gravel-Bed Rivers*, pp. 43–79.
- Dunne, T. and Leopold, L. B.: 1978, *Water in Environmental Planning*, New York, W.H. Freeman and Company, 818 p.
- Fore, L. S., Karr, J. R. and Wisseman, R. W.: 1996, 'Assessing invertebrate responses to human activities: Evaluating alternative approaches', *J. N. Am. Benthol. Soc.* **15**, 212–231.
- Galli, J.: 1996a, *Rapid Stream Assessment Technique (RSAT) Field Methods*, Metropolitan Washington Council of Governments, Department of Environmental Programs, Washington, DC, 36 pp.
- Galli, J.: 1996b, 'Development and Application of the Rapid Stream Assessment Technique (RSAT) in the Maryland Piedmont', in: L. A. Roesner (ed.), *Effects of Watershed Development and Management on Aquatic Ecosystems*, Engineering Foundation Conference, *Proceedings*, Snowbird, Utah, August 4–9, 1996, pp. 295–305.
- Grette, G. B.: 1985, 'The Role of Large Organic Debris in Juvenile Salmonid Rearing Habitat in Small Streams', *Masters Thesis*, University of Washington, Seattle, WA.
- Hankin, D. G. and Reeves, G. H.: 1988, 'Estimating total fish abundance and total habitat area in small streams based on visual estimation methods', *Can. J. Fish. Aquat. Sci.* **45**, 834–844.
- Harris, C. D.: 1987, 'A Summary of the Effects of Streamside Logging Treatments on Organic Debris in Carnation Creek', in: T. W. Chamberlain (ed.), *Proceedings of the Workshop: Applying 15 Years of Carnation Creek Results*, 26–30.
- Henshaw, P. C.: 1999, Restabilization of Stream Channels in Urban Watersheds, *Masters Thesis*, University of Washington, Seattle, USA, 98 p.
- Henshaw, P. C. and Both, D. B.: 'Restabilization of stream channels in urban watersheds', *J. Amer. Water Res. Assoc.*, (in press).
- Hollis, G. E.: 1975, 'The effects of urbanization on floods of difference intervals', *Water Res. Res.* **11**, 431–435.
- Horner, R. R., Booth, D. B., Azous, A. A. and May, C. W.: 1997, 'Watershed Determinants of Ecosystem Functioning', in: L. A. Roesner (ed.), *Effects of Watershed Development and Management on Aquatic Ecosystems*, Engineering Foundation Conference, *Proceedings*, Snowbird, Utah, August 4–9, 1996, pp. 251–274.
- Johnson, P. A. and Heil, T. M.: 1996, 'Uncertainty in estimating bankfull conditions', *Water Res. Bull.* **32**(6), 1283–1291.
- Karr, J. R.: 1998, 'Rivers as Sentinels: Using the Biology of Rivers to Guide Landscape Management', in: R. J. Naiman and R. E. Bilby (eds.), *River Ecology and Management: Lessons from the Pacific Coastal Ecoregion*, New York, Springer, pp. 502–528.

- Karr, J. R. and Chu, E. W.: 1999, *Restoring Life in Running Waters*, Washington, DC, Island Press, 206 p.
- Kondolf, G. M.: 1997, 'Application of the pebble count: notes on purpose, method, and variants', *J. Amer. Water Res. Assoc.* **33**(1), 79–87.
- Lemmon, P. E.: 1957, 'A new instrument for measuring forest overstory density', *J. Forestry* **55**(9), 667–669.
- Leopold, L. B.: 1973, 'River channel change with time – An example', *Geol. Soc. Amer. Bull.* **84**, 1845–1860.
- MacDonald, L. H., Smart, A. W. and Wissmar, R. C.: 1991, *Monitoring Guidelines to Evaluate Effects of Forestry Activities on Streams in the Pacific Northwest and Alaska*, Seattle, Washington, U.S. Environmental Protection Agency Region 10, Water Division, EPA/910/9-91-001, 166 p.
- May, C. W.: 1996, Assessment of Cumulative Effects of Urbanization on Small Streams in the Puget Sound Lowland Ecoregion: Implications for Salmonid Resource Management, *Ph. D. dissertation*, Seattle, University of Washington, Department of Civil Engineering, 383 p.
- Montgomery, D. R. and Buffington, J. M.: 1997, 'Channel reach morphology in mountain drainage basins', *Geol. Soc. Amer. Bull.* **109**, 96–611.
- Montgomery, D. R., Buffington, J. M., Smit, R. D., Schmidt, K. M. and Pess, K.: 1995, 'Pool spacing in forest channels', *Water Res. Res.* **31**(4), 1097–1105.
- Myers, T. J. and Swanson, S.: 1997, 'Precision of channel width and pool area measurements', *J. Amer. Water Res. Assoc.* **33**(3), 647–659.
- Oregon Department of Forestry: 1995, *A Guide to Placing Large Wood in Streams*, Salem, OR, Forest Practices Section, 13 p.
- Peterson, N. P., Hendry, A. and Quinn, T. P.: 1992, *Assessment of Cumulative Effects on Salmonid Habitat: Some Suggested Parameters and Target Conditions*, Seattle, University of Washington, Center for Streamside Studies, publ. TFW-F3-92-001.
- Platts, W. S., Megahan, W. F. and Minshall, G. W.: 1983, Methods Stream, Riparian, and Biotic Conditions, *General Technical Report INT-138*, U.S. Department of Agriculture, Forest Service, Intermountain Forest and Range Experiment Station, Ogden, UT.
- Poole, G. C., Frissell, C. A. and Ralph, S. C.: 1997, 'Instream habitat unit classification: Inadequacies for monitoring and some consequences for management', *J. Amer. Water Res. Assoc.* **33**(4), 879–896.
- Ralph, S. C., Cardoso, T., Poole, G. C., Conquest, L. L. and Naiman, R. J.: 1991, *Status and Trends of Instream Habitat in Forested Lands of Washington*, Seattle, University of Washington, Center for Streamside Studies, biennial progress report.
- Ralph, S. C., Poole, G. C., Conquest, L. L. and Naiman, R. J.: 1994, 'Stream channel morphology and woody debris in logged and unlogged basins of western Washington', *Can. J. Fish. Aquat. Sci.* **51**, 37–51.
- Reid, L. M. and Dunne, T.: 1996, *Rapid Evaluation of Sediment Budgets*, Catena Verlag GmbH, Germany, 164 p.
- Robinson, E. G. and Kaufman, P. R.: 1994, Evaluating two objective techniques to define pools in small streams, in American Water Resources Association, Summer Symposium, *Effects of Human-Induced Changes in Hydrologic Systems*, Jackson Hole, Wyoming, 659–668.
- Roper, B. B. and Scarnecchia, D. L.: 1995, 'Observer variability in classifying habitat types in stream surveys', *North Amer. J. Fish. Man.* **15**, 49–53.
- Rosgen, D. L.: 1994, 'A classification of natural rivers', *Catena* **22**, 169–199.
- Steedman, R. J.: 1988, 'Modification and assessment of an index of biotic integrity to quantify stream quality in southern Ontario', *Can. J. Fish. Aquat. Sci.* **45**, 492–501.
- Swanson, F. J., Lienkaemper, G. W. and Sedell, J. R.: 1976, History, Physical Effects, and Management Implications of Large Organic Debris in Western Oregon Streams, Portland, Oregon, USDA Forest Service, *General Technical Report PNW-56*, Pacific Northwest Forest and Range Experimental Station.

- Warren, C. E., Liss, W. J., Wevers, M. J. *et al.*: 1987, *Artificial Streams from Ecosystem Toxicity Studies*, Corvallis, OR, Oregon State University, Oak Creek Laboratory of Biology, publ. EA-5079.
- Williams, G. P.: 1978, 'Bank-full discharge of rivers', *Water Res. Res.* **14**, 1141–1154.
- Wolman, M. G.: 1954, 'A method of sampling coarse bed material', *Trans. Amer. Geophys. Union* **35**, 951–956.
- Wydzga, A.: 1997, Effects of Urbanization on Fine Sediment Deposition in Puget Sound Lowland Streams, *Masters Thesis*, University of Washington, Seattle WA.