

Homework 6 (MIDTERM #2): Regression and Sparsity

DUE: Monday, December 14, 2020

Download the MNIST data set (both training and test sets and labels): <http://yann.lecun.com/exdb/mnist/>.

The labels will tell you which digit it is: 1, 2, 3, 4, 5, 6, 7, 8, 9, 0. Let each output be denoted by the vector \mathbf{y}_j .

$$\text{"1"} = \begin{bmatrix} 1 \\ 0 \\ 0 \\ \vdots \\ 0 \\ 0 \end{bmatrix}, \text{"2"} = \begin{bmatrix} 0 \\ 1 \\ 0 \\ \vdots \\ 0 \\ 0 \end{bmatrix}, \dots, \text{"9"} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ \vdots \\ 1 \\ 0 \end{bmatrix}, \text{"0"} = \begin{bmatrix} 0 \\ 0 \\ 0 \\ \vdots \\ 0 \\ 1 \end{bmatrix} \quad (1)$$

Now let \mathbf{B} be the set of output vectors

$$\mathbf{B} = [\mathbf{y}_1 \ \mathbf{y}_2 \ \mathbf{y}_3 \ \cdots \ \mathbf{y}_n] \quad (2)$$

and let the matrix \mathbf{A} be the corresponding reshaped (vectorized) MNIST images

$$\mathbf{A} = [\mathbf{x}_1 \ \mathbf{x}_2 \ \mathbf{x}_3 \ \cdots \ \mathbf{x}_n] \quad (3)$$

Thus each vector $\mathbf{x}_j \in \mathbb{R}^{n^2}$ is an a vector reshaped from the $n \times n$ image.

1. Using various $\mathbf{AX} = \mathbf{B}$ solvers, determine a mapping from the image space to the label space.
2. By promoting sparsity, determine and rank which pixels in the MNIST set are most informative for correctly labeling the digits. (You'll have to come up with your own heuristics or empirical rules for this. Use `pcolor` to help you visualize the results from \mathbf{X})
3. Apply your most important pixels to the test data set to see how accurate you are with as few pixels as possible.
4. Redo the analysis with each digit individually to find the most important pixels for each digit.
5. IMPORTANT: Think about the interpretation of what you are doing with this $\mathbf{AX} = \mathbf{B}$ problem.

This is an exploratory homework. So play around with the data and make sure to make lots of plots. Good luck, and have fun.