

VECTOR DERIVATIVES

Cartesian. $d\mathbf{l} = dx \hat{\mathbf{x}} + dy \hat{\mathbf{y}} + dz \hat{\mathbf{z}}$; $d\tau = dx dy dz$

$$\text{Gradient: } \nabla t = \frac{\partial t}{\partial x} \hat{\mathbf{x}} + \frac{\partial t}{\partial y} \hat{\mathbf{y}} + \frac{\partial t}{\partial z} \hat{\mathbf{z}}$$

$$\text{Divergence: } \nabla \cdot \mathbf{v} = \frac{\partial v_x}{\partial x} + \frac{\partial v_y}{\partial y} + \frac{\partial v_z}{\partial z}$$

$$\text{Curl: } \nabla \times \mathbf{v} = \left(\frac{\partial v_z}{\partial y} - \frac{\partial v_y}{\partial z} \right) \hat{\mathbf{x}} + \left(\frac{\partial v_x}{\partial z} - \frac{\partial v_z}{\partial x} \right) \hat{\mathbf{y}} + \left(\frac{\partial v_y}{\partial x} - \frac{\partial v_x}{\partial y} \right) \hat{\mathbf{z}}$$

$$\text{Laplacian: } \nabla^2 t = \frac{\partial^2 t}{\partial x^2} + \frac{\partial^2 t}{\partial y^2} + \frac{\partial^2 t}{\partial z^2}$$

Spherical. $d\mathbf{l} = dr \hat{\mathbf{r}} + r d\theta \hat{\theta} + r \sin \theta d\phi \hat{\phi}$; $d\tau = r^2 \sin \theta dr d\theta d\phi$

$$\text{Gradient: } \nabla t = \frac{\partial t}{\partial r} \hat{\mathbf{r}} + \frac{1}{r} \frac{\partial t}{\partial \theta} \hat{\theta} + \frac{1}{r \sin \theta} \frac{\partial t}{\partial \phi} \hat{\phi}$$

$$\text{Divergence: } \nabla \cdot \mathbf{v} = \frac{1}{r^2} \frac{\partial}{\partial r} (r^2 v_r) + \frac{1}{r \sin \theta} \frac{\partial}{\partial \theta} (\sin \theta v_\theta) + \frac{1}{r \sin \theta} \frac{\partial v_\phi}{\partial \phi}$$

$$\begin{aligned} \text{Curl: } \nabla \times \mathbf{v} &= \frac{1}{r \sin \theta} \left[\frac{\partial}{\partial \theta} (\sin \theta v_\phi) - \frac{\partial v_\theta}{\partial \phi} \right] \hat{\mathbf{r}} \\ &\quad + \frac{1}{r} \left[\frac{1}{\sin \theta} \frac{\partial v_r}{\partial \phi} - \frac{\partial}{\partial r} (r v_\phi) \right] \hat{\theta} + \frac{1}{r} \left[\frac{\partial}{\partial r} (r v_\theta) - \frac{\partial v_r}{\partial \theta} \right] \hat{\phi} \end{aligned}$$

$$\text{Laplacian: } \nabla^2 t = \frac{1}{r^2} \frac{\partial}{\partial r} \left(r^2 \frac{\partial t}{\partial r} \right) + \frac{1}{r^2 \sin \theta} \frac{\partial}{\partial \theta} \left(\sin \theta \frac{\partial t}{\partial \theta} \right) + \frac{1}{r^2 \sin^2 \theta} \frac{\partial^2 t}{\partial \phi^2}$$

Cylindrical. $d\mathbf{l} = ds \hat{\mathbf{s}} + s d\phi \hat{\phi} + dz \hat{\mathbf{z}}$; $d\tau = s ds d\phi dz$

$$\text{Gradient: } \nabla t = \frac{\partial t}{\partial s} \hat{\mathbf{s}} + \frac{1}{s} \frac{\partial t}{\partial \phi} \hat{\phi} + \frac{\partial t}{\partial z} \hat{\mathbf{z}}$$

$$\text{Divergence: } \nabla \cdot \mathbf{v} = \frac{1}{s} \frac{\partial}{\partial s} (s v_s) + \frac{1}{s} \frac{\partial v_\phi}{\partial \phi} + \frac{\partial v_z}{\partial z}$$

$$\text{Curl: } \nabla \times \mathbf{v} = \left[\frac{1}{s} \frac{\partial v_z}{\partial \phi} - \frac{\partial v_\phi}{\partial z} \right] \hat{\mathbf{s}} + \left[\frac{\partial v_s}{\partial z} - \frac{\partial v_z}{\partial s} \right] \hat{\phi} + \frac{1}{s} \left[\frac{\partial}{\partial s} (s v_\phi) - \frac{\partial v_s}{\partial \phi} \right] \hat{\mathbf{z}}$$

$$\text{Laplacian: } \nabla^2 t = \frac{1}{s} \frac{\partial}{\partial s} \left(s \frac{\partial t}{\partial s} \right) + \frac{1}{s^2} \frac{\partial^2 t}{\partial \phi^2} + \frac{\partial^2 t}{\partial z^2}$$

FUNDAMENTAL CONSTANTS

$$\epsilon_0 = 8.85 \times 10^{-12} \text{ C}^2/\text{Nm}^2 \quad (\text{permittivity of free space})$$

$$\mu_0 = 4\pi \times 10^{-7} \text{ N/A}^2 \quad (\text{permeability of free space})$$

$$c = 3.00 \times 10^8 \text{ m/s} \quad (\text{speed of light})$$

$$e = 1.60 \times 10^{-19} \text{ C} \quad (\text{charge of the electron})$$

$$m = 9.11 \times 10^{-31} \text{ kg} \quad (\text{mass of the electron})$$

SPHERICAL AND CYLINDRICAL COORDINATES

Spherical

$$\begin{cases} x = r \sin \theta \cos \phi \\ y = r \sin \theta \sin \phi \\ z = r \cos \theta \end{cases} \quad \begin{cases} \hat{\mathbf{x}} = \sin \theta \cos \phi \hat{\mathbf{r}} + \cos \theta \cos \phi \hat{\theta} - \sin \phi \hat{\phi} \\ \hat{\mathbf{y}} = \sin \theta \sin \phi \hat{\mathbf{r}} + \cos \theta \sin \phi \hat{\theta} + \cos \phi \hat{\phi} \\ \hat{\mathbf{z}} = \cos \theta \hat{\mathbf{r}} - \sin \theta \hat{\theta} \end{cases}$$

$$\begin{cases} r = \sqrt{x^2 + y^2 + z^2} \\ \theta = \tan^{-1}(\sqrt{x^2 + y^2}/z) \\ \phi = \tan^{-1}(y/x) \end{cases} \quad \begin{cases} \hat{\mathbf{r}} = \sin \theta \cos \phi \hat{\mathbf{x}} + \sin \theta \sin \phi \hat{\mathbf{y}} + \cos \theta \hat{\mathbf{z}} \\ \hat{\theta} = \cos \theta \cos \phi \hat{\mathbf{x}} + \cos \theta \sin \phi \hat{\mathbf{y}} - \sin \theta \hat{\mathbf{z}} \\ \hat{\phi} = -\sin \phi \hat{\mathbf{x}} + \cos \phi \hat{\mathbf{y}} \end{cases}$$

Cylindrical

$$\begin{cases} x = s \cos \phi \\ y = s \sin \phi \\ z = z \end{cases} \quad \begin{cases} \hat{\mathbf{x}} = \cos \phi \hat{\mathbf{s}} - \sin \phi \hat{\phi} \\ \hat{\mathbf{y}} = \sin \phi \hat{\mathbf{s}} + \cos \phi \hat{\phi} \\ \hat{\mathbf{z}} = \hat{\mathbf{z}} \end{cases}$$

$$\begin{cases} s = \sqrt{x^2 + y^2} \\ \phi = \tan^{-1}(y/x) \\ z = z \end{cases} \quad \begin{cases} \hat{\mathbf{s}} = \cos \phi \hat{\mathbf{x}} + \sin \phi \hat{\mathbf{y}} \\ \hat{\phi} = -\sin \phi \hat{\mathbf{x}} + \cos \phi \hat{\mathbf{y}} \\ \hat{\mathbf{z}} = \hat{\mathbf{z}} \end{cases}$$

$$\mathbf{F} = \frac{1}{4\pi\epsilon_0} \frac{qQ}{r^2} \hat{r} \quad \text{Coulomb's Law} \quad \mathbf{F} = Q\mathbf{E} + Q\mathbf{v} \times \mathbf{B} \quad \text{Lorentz force}$$

$$\mathbf{E} = \frac{1}{4\pi\epsilon_0} \iiint \frac{\rho(\mathbf{r}')}{r'^2} \hat{r} d\tau' \quad \text{electric field from continuous charge distribution}$$

$$\oint\oint \mathbf{E} \cdot d\mathbf{a} = \frac{1}{\epsilon_0} Q_{\text{encl}} \text{ Gauss' Law (integral)} \quad \oint \mathbf{E} \cdot d\mathbf{l} = 0 \text{ (statics)}$$

$$V(\mathbf{r}) = - \int_{\varphi}^{\mathbf{r}} \mathbf{E} \cdot d\mathbf{l} \text{ Electrostatic potential, and } \mathbf{E} = -\nabla V \text{ (statics)}$$

$$\nabla^2 V = -\frac{\rho}{\epsilon_0} \text{ Poisson's equation, and } \nabla^2 V = 0 \text{ Laplace's equation (regions of no charge)}$$

$$V(\mathbf{r}) = \frac{1}{4\pi\epsilon_0} \frac{q}{r} \text{ and } V(\mathbf{r}) = \frac{1}{4\pi\epsilon_0} \iiint \frac{\rho(\mathbf{r}')}{r} d\tau' \text{ (setting reference point at infinity)}$$

$$\mathbf{E}_{\text{above}} - \mathbf{E}_{\text{below}} = \frac{\sigma}{\epsilon_0} \hat{\mathbf{n}} \text{ and } \frac{\partial V_{\text{above}}}{\partial n} - \frac{\partial V_{\text{below}}}{\partial n} = \frac{1}{\epsilon_0} \sigma \text{ boundary conditions}$$

$$D_{\text{above}}^\perp - D_{\text{below}}^\perp = \sigma_f$$

$$V(\mathbf{b}) - V(\mathbf{a}) = \frac{W}{Q} \quad W = \frac{1}{2} \sum_{i=1}^n q_i V(\mathbf{r}_i) \text{ and } W = \frac{1}{2} \iiint \rho V d\tau$$

$$Q = CV \quad W = \frac{1}{2} CV^2 \quad W = \frac{1}{2} Q^2 / C \text{ capacitors}$$

$$\nabla^2 V = -\frac{1}{\epsilon_0} \rho \text{ Poisson's equation} \quad \nabla^2 V = 0 \text{ Laplace's equation}$$

$$V(x, y) = \sum_{n=0}^{\infty} (A_n e^{+kx} + B_n e^{-kx})(C_n \sin ky + D_n \cos ky) \text{ solution to Laplace's equation in Cartesian coordinates in two dimensions}$$

$$\int_0^a \sin(n\pi \frac{y}{a}) \sin(n'\pi \frac{y}{a}) dy = \begin{cases} 0 & n \neq n' \\ \frac{a}{2} & n = n' \end{cases} \text{ orthogonality of sines}$$

$$\int_0^a \sin(n\pi \frac{y}{a}) dy = \begin{cases} 0 & n \text{ even} \\ \frac{2a}{n\pi} & n \text{ odd} \end{cases} \quad e^{+kx} + e^{-kx} = 2 \cosh kx$$

$$\int_0^\pi \cos^2 \theta \sin \theta d\theta = 2/3$$

$P_0(x) = 1$
$P_1(x) = x$
$P_2(x) = (3x^2 - 1)/2$
$P_3(x) = (5x^3 - 3x)/2$
$P_4(x) = (35x^4 - 30x^2 + 3)/8$
$P_5(x) = (63x^5 - 70x^3 + 15x)/8$

$$V(r, \theta) = \sum_{\ell=0}^{\infty} \left(A_\ell r^\ell + \frac{B_\ell}{r^{\ell+1}} \right) P_\ell(\cos \theta)$$

TABLE 3.1 Legendre Polynomials.

solution to Laplace's equation in spherical coordinates with azimuthal symmetry

$$\int_0^\pi P_\ell(\cos \theta) P_{\ell'}(\cos \theta) d\cos \theta = \begin{cases} 0 & \ell \neq \ell' \\ \frac{2}{2\ell+1} & \ell = \ell' \end{cases} \quad \text{orthogonality of Legendre polynomials}$$

$$V(r, \theta) = -E_0 \left(r - \frac{R^3}{r^2} \right) \cos \theta \quad \text{potential outside a neutral conducting sphere in uniform field}$$

Law of cosines $c^2 = a^2 + b^2 - 2ab \cos \gamma$, with γ the angle opposite to side c .

$$\frac{1}{r} = \frac{1}{r} \sum_0^{\infty} \left(\frac{r'}{r} \right)^n P_n(\cos \alpha) \quad 1/r \text{ expansion in Legendre polynomials}$$

$$V(r) = \frac{1}{4\pi\epsilon_0} \sum_0^{\infty} \frac{1}{r^{n+1}} \iiint (r')^n P_n(\cos \alpha) \rho(\mathbf{r}') d\tau' \quad \text{multipole expansion}$$

$$\vec{p} = \iiint \vec{r}' \rho(\vec{r}') d\tau' \quad \vec{p} = \sum_1^n q_i \vec{r}_i \quad V_{\text{dip}}(\vec{r}) = \frac{1}{4\pi\epsilon_0} \frac{\vec{p} \cdot \hat{r}}{r^2} \quad \text{dipole moment}$$

$$\vec{E}_{\text{dip}} = \frac{p}{4\pi\epsilon_0 r^3} (2 \cos \theta \hat{r} + \sin \theta \hat{\theta})$$

$$\mathbf{F}_{\text{mag}} = \int I d\mathbf{l} \times \mathbf{B}$$

$$\mathbf{K} = d\mathbf{I}/d\ell_{\perp} \quad \mathbf{J} = d\mathbf{I}/da_{\perp} \quad \text{surface and volume currents}$$

$$\nabla \cdot \mathbf{J} + \frac{d\rho}{dt} = 0 \quad \text{conserved current}$$

$$\mathbf{B}(\mathbf{r}) = \frac{\mu_0}{4\pi} I \int \frac{d\mathbf{l}' \times \hat{r}}{|\mathbf{r} - \mathbf{r}'|^2} \quad \mathbf{B}(\mathbf{r}) = \frac{\mu_0}{4\pi} \int \frac{\mathbf{K} \times \hat{r}}{|\mathbf{r} - \mathbf{r}'|^2} da' \quad \mathbf{B}(\mathbf{r}) = \frac{\mu_0}{4\pi} I \int \frac{\mathbf{J} \times \hat{r}}{|\mathbf{r} - \mathbf{r}'|^2} d\tau'$$

$$\oint \mathbf{B} \cdot d\mathbf{l} = \mu_0 I_{\text{enc}}$$

$\mathbf{B} = \nabla \times \mathbf{A}$ magnetic vector potential.

$\nabla \cdot \mathbf{A} = 0$ “Coulomb gauge” convention $\nabla^2 \mathbf{A} = -\mu_0 \mathbf{J}$ (for Coulomb gauge)

$$\mathbf{A}(\mathbf{r}) = \frac{\mu_0}{4\pi} \int \frac{\mathbf{J}(\mathbf{r}')}{|\mathbf{r} - \mathbf{r}'|} d\mathbf{l}' \quad \mathbf{A}(\mathbf{r}) = \frac{\mu_0}{4\pi} \int \frac{\mathbf{K}(\mathbf{r}')}{|\mathbf{r} - \mathbf{r}'|} da' \quad \mathbf{A}(\mathbf{r}) = \frac{\mu_0}{4\pi} \int \frac{I}{|\mathbf{r} - \mathbf{r}'|} d\mathbf{l}'$$

$$\oint \mathbf{A} \cdot d\mathbf{l} = \Phi_m$$

$$B_{\text{above}}^\perp - B_{\text{below}}^\perp = 0 \quad B_{\text{above}}^\parallel - B_{\text{below}}^\parallel = \mu_0 K \quad \mathbf{B}_{\text{above}} - \mathbf{B}_{\text{below}} = \mu_0 \mathbf{K} \times \hat{n}$$

$$\mathbf{A}_{\text{above}} - \mathbf{A}_{\text{below}} = 0 \quad \frac{\partial \mathbf{A}_{\text{above}}}{\partial n} - \frac{\partial \mathbf{A}_{\text{below}}}{\partial n} = -\mu_0 \mathbf{K}$$

$$\mathbf{m} = I \iint \hat{n} da = I \mathbf{a}$$

$$\mathbf{m} = \frac{1}{2} \oint \mathbf{r} \times \mathbf{I} d\ell \quad \mathbf{m} = \frac{1}{2} \iint \mathbf{r} \times \mathbf{K} da \quad \mathbf{m} = \frac{1}{2} \iiint \mathbf{r} \times \mathbf{J} d\tau$$

$$\mathbf{A}_{\text{dip}}(\mathbf{r}) = \frac{\mu_0}{4\pi} \frac{\mathbf{m} \times \hat{r}}{r^2}$$

$$\mathbf{N} = \mathbf{m} \times \mathbf{B} \quad \mathbf{F} = \nabla(\mathbf{m} \cdot \mathbf{B}) \quad U = -\mathbf{m} \cdot \mathbf{B}$$

$$\mathbf{J}_b = \nabla \times \mathbf{M} \quad \mathbf{K}_b = \mathbf{M} \times \hat{n}$$

$$\mathbf{H} = \frac{1}{\mu_0} \mathbf{B} - \mathbf{M} \quad \nabla \times \mathbf{H} = \mathbf{J}_f \quad \oint \mathbf{H} \cdot d\mathbf{l} = I_{\text{f, encl}}$$

$$H_{\text{above}}^\perp - H_{\text{below}}^\perp = -(M_{\text{above}}^\perp - M_{\text{below}}^\perp) \quad \mathbf{H}_{\text{above}}^\parallel - \mathbf{H}_{\text{below}}^\parallel = \mathbf{K}_f \times \hat{n}$$

$$\mathbf{M} = \chi_m \mathbf{H} \quad \mu = \mu_0 (1 + \chi_m) \quad \mathbf{B} = \mu \mathbf{H}$$

$$\mathbf{J} = \sigma \mathbf{E} \quad V = IR \quad P = VI = I^2 R$$

$$\mathcal{E} = \oint \mathbf{E} \cdot d\ell \quad \mathcal{E} = -\frac{d\Phi_M}{dt}$$

$$\Phi_2 = M I_1 \quad \Phi = LI \quad \mathcal{E}_2 = -M \frac{dI_1}{dt} \quad \mathcal{E} = -L \frac{dI}{dt} \quad W = \frac{1}{2} LI^2$$

$$\mathbf{S} = \frac{1}{\mu_0} \mathbf{E} \times \mathbf{B} \quad I = \langle \mathbf{S} \rangle$$

$$\nabla \cdot \left(\frac{1}{\mu_0} \mathbf{E} \times \mathbf{B} \right) + \frac{\partial}{\partial t} \left(\frac{\epsilon_0}{2} E^2 + \frac{1}{2\mu_0} B^2 \right) = -\mathbf{E} \cdot \mathbf{J} \quad \text{Poynting's theorem (differential)}$$

$$\frac{dW}{dt} = -\frac{d}{dt} \iiint \left(\frac{\epsilon_0}{2} E^2 + \frac{1}{2\mu_0} B^2 \right) d\tau - \iint \left(\frac{1}{\mu_0} \mathbf{E} \times \mathbf{B} \right) \cdot \hat{n} da \quad \text{Poynting's thm (integral)}$$

$$dF_i = T_{ij} da_j \quad \frac{dF_i}{d\tau_i} = \frac{\partial T_{ij}}{\partial x_j} \quad T_{ij} = \epsilon_0 \left(E_i E_j - \frac{1}{2} \delta_{ij} E^2 \right) + \frac{1}{\mu_0} \left(B_i B_j - \frac{1}{2} \delta_{ij} B^2 \right)$$

$$\frac{d}{dt} \left(P_i(\text{mech}) + P_i(\text{fields}) \right) = \iint T_{ij} a_j \frac{d}{d\tau} \mathbf{P}(\text{fields}) = \mu_0 \epsilon_0 \mathbf{S} \cdot \frac{d}{d\tau} \mathbf{L}(\text{fields}) = \mathbf{r} \times \mu_0 \epsilon_0 \mathbf{S}$$

$$\frac{\partial^2 f}{\partial z^2} - \frac{1}{V^2} \frac{\partial^2 f}{\partial t^2} = 0 \quad \lambda = 2\pi/k \quad T = 2\pi/kV \quad \nu = 1/T \quad \omega = 2\pi\nu = kV$$

$$e^{i\theta} = \cos\theta + i\sin\theta$$

$$\text{vacuum} \quad \nabla^2 \mathbf{E} - \mu_0 \epsilon_0 \frac{\partial^2 \mathbf{E}}{\partial t^2} = 0 \quad \nabla^2 \mathbf{B} - \mu_0 \epsilon_0 \frac{\partial^2 \mathbf{B}}{\partial t^2} = 0 \quad c = 1/\sqrt{\mu_0 \epsilon_0}$$

$$\tilde{\mathbf{E}}(z,t) = \tilde{\mathbf{E}}_0 e^{i(kz-\omega t)} \quad \tilde{\mathbf{B}}(z,t) = \tilde{\mathbf{B}}_0 e^{i(kz-\omega t)} \quad E_0 = cB_0$$

$$\langle u \rangle = \frac{1}{2} \epsilon_0 E_0^2 \quad \langle \mathbf{S} \rangle = \frac{1}{2} c \epsilon_0 E_0^2 \hat{k} \quad I = \langle S \rangle \quad \langle \mathbf{p} \rangle = \frac{1}{2c} \epsilon_0 E_0^2 \hat{k}$$

$$\text{lossless} \quad \nabla^2 \mathbf{E} - \mu \epsilon \frac{\partial^2 \mathbf{E}}{\partial t^2} = 0 \quad \nabla^2 \mathbf{B} - \mu \epsilon \frac{\partial^2 \mathbf{B}}{\partial t^2} = 0 \quad V = 1/\sqrt{\mu \epsilon} = c/n \quad n = \sqrt{\mu \epsilon / \mu_0 \epsilon_0}$$

$$u = \frac{1}{2} \left(\epsilon E^2 + \frac{1}{\mu} B^2 \right) \quad \mathbf{S} = \frac{1}{\mu} \mathbf{E} \times \mathbf{B} \quad I = \frac{1}{2} \epsilon V E_0^2$$

$$\theta_i = \theta_r \quad n_1 \sin \theta_i = n_2 \sin \theta_t \quad R = I_r / I_i \quad T = I_t / I_i$$

$$\left. \frac{E_{0r}}{E_{0i}} \right|_{\perp} = \frac{\frac{n_1}{\mu_1} \cos \theta_i - \frac{n_2}{\mu_2} \cos \theta_t}{\frac{n_1}{\mu_1} \cos \theta_i + \frac{n_2}{\mu_2} \cos \theta_t} \quad \left. \frac{E_{0t}}{E_{0i}} \right|_{\perp} = \frac{2 \frac{n_1}{\mu_1} \cos \theta_i}{\frac{n_1}{\mu_1} \cos \theta_i + \frac{n_2}{\mu_2} \cos \theta_t}$$

$$\left. \frac{E_{0r}}{E_{0i}} \right|_{\parallel} = \frac{-\frac{n_2}{\mu_2} \cos \theta_i + \frac{n_1}{\mu_1} \cos \theta_t}{\frac{n_2}{\mu_2} \cos \theta_i + \frac{n_1}{\mu_1} \cos \theta_t} \quad \left. \frac{E_{0t}}{E_{0i}} \right|_{\parallel} = \frac{2 \frac{n_1}{\mu_1} \cos \theta_t}{\frac{n_2}{\mu_2} \cos \theta_i + \frac{n_1}{\mu_1} \cos \theta_t}$$

$$\tan \theta_B \cong n_2 / n_1 \quad \sin \theta_c = n_2 / n_1$$

$$7 \\$$

Maxwell's Equations

In general:

$$\left\{ \begin{array}{l} \nabla \cdot \mathbf{E} = \frac{1}{\epsilon_0} \rho \\ \nabla \times \mathbf{E} = -\frac{\partial \mathbf{B}}{\partial t} \\ \nabla \cdot \mathbf{B} = 0 \\ \nabla \times \mathbf{B} = \mu_0 \mathbf{J} + \mu_0 \epsilon_0 \frac{\partial \mathbf{E}}{\partial t} \end{array} \right.$$

In matter:

$$\left\{ \begin{array}{l} \nabla \cdot \mathbf{D} = \rho_f \\ \nabla \times \mathbf{E} = -\frac{\partial \mathbf{B}}{\partial t} \\ \nabla \cdot \mathbf{B} = 0 \\ \nabla \times \mathbf{H} = \mathbf{J}_f + \frac{\partial \mathbf{D}}{\partial t} \end{array} \right.$$

Auxiliary Fields

Definitions:

$$\left\{ \begin{array}{l} \mathbf{D} = \epsilon_0 \mathbf{E} + \mathbf{P} \\ \mathbf{H} = \frac{1}{\mu_0} \mathbf{B} - \mathbf{M} \end{array} \right.$$

Linear media:

$$\left\{ \begin{array}{l} \mathbf{P} = \epsilon_0 \chi_e \mathbf{E}, \quad \mathbf{D} = \epsilon \mathbf{E} \\ \mathbf{M} = \chi_m \mathbf{H}, \quad \mathbf{H} = \frac{1}{\mu} \mathbf{B} \end{array} \right.$$

Potentials

$$\mathbf{E} = -\nabla V - \frac{\partial \mathbf{A}}{\partial t}, \quad \mathbf{B} = \nabla \times \mathbf{A}$$

Lorentz force law

$$\mathbf{F} = q(\mathbf{E} + \mathbf{v} \times \mathbf{B})$$

Energy, Momentum, and Power

$$Energy: \quad U = \frac{1}{2} \int \left(\epsilon_0 E^2 + \frac{1}{\mu_0} B^2 \right) d\tau$$

$$Momentum: \quad \mathbf{P} = \epsilon_0 \int (\mathbf{E} \times \mathbf{B}) d\tau$$

$$Poynting vector: \quad \mathbf{S} = \frac{1}{\mu_0} (\mathbf{E} \times \mathbf{B})$$