

1

2

3

4

5

6

MATERIAL / PACE

- Please classify your perspective on material covered in today's class (32 of 46 respondents – 69.5%) :
- ***SURVEY ISSUE***: Canvas Survey Initially Unavailable, NOW POSTED AND AVAILABLE until Mon Jan 26
- 1-mostly review, 5-equal new/review, 10-mostly new
- Average – 7.03 (↑ - previous 6.54)
- Please rate the pace of today's class:
- 1-slow, 5-just right, 10-fast
- Average – 5.08 (↑ - previous 4.73)

January 22, 2026

TCSS422: Computer Operating Systems (Spring 2025)
School of Engineering and Technology, University of Washington - Tacoma

LS.7

7

FEEDBACK FROM 1/20

- Where would you use a fork() ?
- The fork() API is used to create a new process in Linux
- *What is strange* –how new processes are created in Linux
- Instead of creating a brand-new squeaky-clean process, with an empty heap, stack, & data segments, fork() clones the existing process
- A complete copy of the parent process is made – BUT...
 - The copy is made using COW: copy on write
 - Memory is only cloned when data changes
- COW allows fork() to occur in a huge program, while actually doing minimal memory cloning

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.8

8

FEEDBACK - 2

- Does OS always fork the parent process? Or is there any case to fork the child process?
- The fork() API can be called inside any process, to clone the existing process, to create a new one
- Inside a main program, you can have nested forks:

```
parent-fork()
/  \
parent child-1-fork()
      /  \
      child-1 child-2-fork()
            /  \
            child2 child3
```

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.9

9

FEEDBACK - 3

- What does the fork bomb do If it doesn't call fork() literally?
- fork() is a C API
- In bash, the fork-bomb creates a function called ":"
- The fork bomb is

```
:(){ :|: & };:
```
- If we rename ":" to "funca", what we are really doing is defining a bash function call "funca":

```
funca() { funca | funca & };
```
- Each call to funca makes 2 more funca calls
- Each funca call is run as a separate process
 - Every command is bash is run as a separate process
- After the funca definition, funca is called (with ":")

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.10

10

FEEDBACK - 4

- How do you call a custom program with the exec APIs ?
- The same as you would call any Linux command
- It must be in the system path
- If your executable is in the present working directory, then "." must be in the path
- Check the path with:

```
echo $PATH
```
- If the executable is not in the path, a fully qualified pathname is required to run the executable
- The 'which' command reports what command will be run
- Myargs should always include the command and arguments

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.11

11

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.12

12

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.13

13

FINISH CHAPTER 5

- Switch to Lecture 4 Slides
- Slides L4.51 to L4.60 (thru system calls and traps)

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.14

14

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples


January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.15

15

CH. 6:
LIMITED DIRECT
EXECUTION



January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.16

16

CHAPTER 6

- Chapter 6: Limited Direct Execution
 - Direct execution
 - Limited direct execution
 - CPU modes
 - System calls and traps
 - Cooperative multi-tasking
 - Context switching and preemptive multi-tasking

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.17

17

MULTITASKING

- How/when should the OS regain control of the CPU to switch between processes?
- Cooperative multitasking (mostly pre 32-bit)
 - < Windows 95, Mac OSX
- Opportunistic: running programs must give up control
 - User programs must call a special **yield** system call
 - When performing I/O
 - Illegal operations
- (POLLEV)
What problems could you see with this approach?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.18

18

MULTITASKING

- How/when should the OS regain control of the CPU to switch between processes?
- Cooperative multitasking (mostly pre-32-bit)
 - A process gets stuck in an infinite loop.
→ Reboot the machine
 - When performing I/O
 - Illegal operations
- (POLLEV)
What problems could you see with this approach?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.19

19

Activities

When poll is active respond at

PollEv.com /weslloyd

Send weslloyd and your message to 22333

W

What problems exist for regaining control of the CPU with cooperative multitasking OSes?

7

Too many processing calling yield at once?

Program has too much control over OS, too much trust to user

SEE MORE

the OS is at the mercy of whomever wrote a

Current responses

20

QUESTION: MULTITASKING

- What problems exist for regaining the control of the CPU with cooperative multitasking OSes?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.21

21

MULTITASKING - 2

- Preemptive multitasking (32 & 64 bit OSes)
 - >= Mac OSX, Windows 95+
- Timer interrupt
 - Raised at some regular interval (in ms)
 - Interrupt handling
 - Current program is halted
 - Program states are saved
 - OS Interrupt handler is run (kernel mode)
- (POLLEV) What is a good interval for the timer interrupt?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.22

22

MULTITASKING - 2

- Preemptive multitasking (32 & 64 bit OSes)
 - >= Mac OSX, Windows 95+
- Timer interrupt
 - A timer interrupt gives OS the ability to run again on a CPU.
 - Raised at some regular interval (in ms)
 - Interrupt handling
 - Current program is halted
 - Program states are saved
 - OS Interrupt handler is run (kernel mode)
- (POLLEV) What is a good interval for the timer interrupt?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.23

23

Activities

When poll is active respond at

PollEv.com /weslloyd

Send weslloyd and your message to 22333

W

For an OS that uses a system timer to force arbitrary context switches to share the CPU, what is a good value (in seconds) for the timer interrupt?

0

Join by Web

Join by Text

Join by QR code

PollEv.com/weslloyd

Send weslloyd and your message to 22333

Scan with your camera app

Current responses

24

QUESTION: TIME SLICE

- For an OS that uses a system timer to force arbitrary context switches to share the CPU, what is a good value (in seconds) for the timer interrupt?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.25

25

QUESTION: TIME SLICE

- For an OS that uses a system timer to force arbitrary context switches to share the CPU, what is a good value (in seconds) for the timer interrupt?
 - Typical time slice for process execution is **10 to 100 milliseconds**
 - Typical context switch overhead is (switch between processes) **0.01 milliseconds**
 - 0.1% of the time slice (1/1000th)

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.26

26

CHAPTER 6

- Chapter 6: Limited Direct Execution
 - Direct execution
 - Limited direct execution
 - CPU modes
 - System calls and traps
 - Cooperative multi-tasking
 - Context switching and preemptive multi-tasking**

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.27

27

CONTEXT SWITCH

- Preemptive multitasking initiates “trap” into the OS code to determine:
 - Whether to continue running the **current process**, or switch to a **different one**.
 - If the decision is made to switch, the OS performs a context switch swapping out the current process for a new one.

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.28

28

CONTEXT SWITCH - 2

- Save register values of the current process to its kernel stack
 - General purpose registers
 - PC: program counter (instruction pointer)
 - kernel stack pointer
- Restore soon-to-be-executing process from its kernel stack
- Switch to the kernel stack for the soon-to-be-executing process

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.29

29

The diagram illustrates the context switch process across three states: OS @ boot (kernel mode), OS @ run (kernel mode), and Program (user mode). In the boot state, the OS initializes a trap table (remembering syscall and timer handler addresses) and starts an interrupt timer (interrupting the CPU every X ms). In the run state, a timer interrupt occurs, saving the current process's registers (A) to its kernel stack (A), moving the PC to the trap handler, and jumping to the trap handler. The trap handler then calls a switch routine, saving the current process's registers (A) to its kernel stack (A), restoring the next process's registers (B) from its kernel stack (B), switching to the next process's kernel stack (B), and returning from the trap (into B). Finally, in the user mode, the registers (B) are restored from the kernel stack (B), the PC is moved to the user mode, and the jump to the next process's PC is executed, starting Process B.

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.30

30

OS @ boot
(kernel mode)

Hardware

initialize trap table

remember address of ...
syscall handler
timer handler

start interrupt timer

start timer
interrupt CPU in X ms

OS @ run
(user mode)

Hardware

Program
(user mode)

Call switch() routine

save reg(A) to proc-struct(A)

restore reg(B) from proc-struct(B)

switch to k-stack(B)

return-from-trap (into B)

restore reg(B) from k-stack(B)

move to user mode

jump to B's PC

Process B

→

Context Switch

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.31

31

CLASS BREAK - QUESTIONS

■ **When dealing with OS control trade-offs, what does an OS have to do so that there is not too much overhead?**

■ OS functions must use fast, lightweight data structures for the process context, and fast scheduling algorithms

■ Context switches must be engineering to occur rapidly

■ Memory virtualization approach (how the system translates between virtual and physical addresses) needs to be super fast

■ CPUs include a special cache to help address translation called the Translation Lookaside Buffer (TLB). Essentially once an address has been translated, the cached translation is used until the address falls out of the cache

■ **Should we memorize Linux terminal commands?**

■ Programming/scripting involves much trial-and-error. Knowing more commands without looking them up enables more trials in less time

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.32

32

EXTRA CREDIT SEMINAR – FRIDAY

■ **Research Talk:** Securing the Blindspots: From Formal Verification to Generative Verification

■ Dr. Shakthi Yasas Weerasinghe, Postdoctoral Research Associate at the University of Arizona

■ Friday Jan 23, 12:20pm - 1:20pm Milgard 110

■ **Abstract:** This seminar explores the critical challenge of "authorization blindspots"—latent security vulnerabilities created when decentralized microservice policies diverge. Attendees will follow a research trajectory designed to detect, and validate these risks through a novel, multi-layered framework. We will first explore Automated Formal Verification, demonstrating how microservice source code can be encoded into SMT constraint models to deterministically identify end-to-end inconsistencies without manual specification. The discussion will then move to Generative Validation, illustrating how formal static analysis can be hybridized with Large Language Models. Participants will see how policy-enriched Intermediate Representations (IR) are used to guide LLMs in generating executable, downstream-aware tests that empirically validate security drifts with high semantic validity.

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.33

33

WE WILL RETURN AT
~4:55PM

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.34

34

INTERRUPTED INTERRUPTS

■ What happens if during an interrupt (trap to kernel mode), another interrupt occurs?

■ Linux

- < 2.6 kernel: non-preemptive kernel
- >= 2.6 kernel: preemptive kernel

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.35

35

PREEMPTIVE KERNEL

■ Use "locks" as markers of regions of non-preemptibility (non-maskable interrupt)

■ Preemption counter (`preempt_count`)

- begins at zero
- increments for each lock acquired (not safe to preempt)
- decrements when locks are released

■ Interrupt can be interrupted when `preempt_count=0`

- It is safe to preempt (maskable interrupt)
- the interrupt is more important

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.36

36

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction**
 - Scheduling metrics**
 - Turnaround time, Jain's Fairness Index**, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples


January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.37

37

CHAPTER 7-
SCHEDULING:
INTRODUCTION



January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.38

38

SCHEDULING METRICS

- Metrics:** A standard measure to quantify to what degree a system possesses some property. Metrics provide repeatable techniques to quantify and compare systems.
- Measurements** are the numbers derived from the application of metrics
- Scheduling Metric #1: **Turnaround time**
- The time at which the job completes minus the time at which the job arrived in the system

$T_{\text{turnaround}} = T_{\text{completion}} - T_{\text{arrival}}$

- How is turnaround time different than execution time?

January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.39

39

SCHEDULING METRICS - 2

- Scheduling Metric #2: **Fairness**
 - Jain's fairness index
 - Quantifies if jobs receive a fair share of system resources

$$J(x_1, x_2, \dots, x_n) = \frac{(\sum_{i=1}^n x_i)^2}{n \cdot \sum_{i=1}^n x_i^2}$$

- n processes
- x_i is time share of each process
- worst case = $1/n$
- best case = 1

- Consider $n=3$, worst case = .333, best case=1
- With $n=3$ and $x_1=.2, x_2=.7, x_3=.1$, fairness=.62
- With $n=3$ and $x_1=.33, x_2=.33, x_3=.33$, fairness=1

January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.40

40

With $n=3$ and $x_1=.2, x_2=.7, x_3=.1$

$$J(x_1, x_2, \dots, x_n) = \frac{(\sum_{i=1}^n x_i)^2}{n \cdot \sum_{i=1}^n x_i^2}$$

$$\frac{1}{3 \cdot (.2)^2 + (.7)^2 + (.1)^2} = \frac{1}{3 \cdot (.04 + .49 + .01)} = \frac{1}{1.62} = .617$$

January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.41

41

With $n=3$ and $x_1=.2, x_2=.7, x_3=.1$

$$J(x_1, x_2, \dots, x_n) = \frac{(\sum_{i=1}^n x_i)^2}{n \cdot \sum_{i=1}^n x_i^2}$$

$$\frac{(.2 + .7 + .1)^2}{3 \cdot (.2)^2 + (.7)^2 + (.1)^2} = \frac{1}{1.62} = .617$$

$$\frac{1}{3 \cdot (.04 + .49 + .01)} = \frac{1}{1.62} = .617$$

$$\frac{1}{3 \cdot (.04 + .49 + .01)} = \frac{1}{1.62} = .617$$

January 22, 2026

TCSS422: Operating Systems [Winter 2026]
School of Engineering and Technology, University of Washington - Tacoma

L5.42

42

With $n=3$ and $x_1=.33, x_2=.33, x_3=.33$

$$\mathcal{J}(x_1, x_2, \dots, x_n) = \frac{(\sum_{i=1}^n x_i)^2}{n \cdot \sum_{i=1}^n x_i^2}$$

$$\frac{1}{3 \cdot (.33^2 + .33^2 + .33^2)} = \frac{1}{3 \cdot (.1089 + .1089 + .1089)} = \frac{1}{3 \cdot (.3267)} = \frac{1}{.9801} \rightarrow 1$$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.43

43

With $n=3$ and $x_1=.33, x_2=.33, x_3=.33$

$$\mathcal{J}(x_1, x_2, \dots, x_n) = \frac{(\sum_{i=1}^n x_i)^2}{n \cdot \sum_{i=1}^n x_i^2}$$

$$\frac{.35 + .35 + .35}{3 \cdot (.35^2 + .35^2 + .35^2)} \rightarrow \frac{1}{3 \cdot (.1225 + .1225 + .1225)} \rightarrow \frac{1}{.9801} \rightarrow 1$$

$$\frac{.3267}{3 \cdot (.3267)} \rightarrow \frac{1}{.9801} \rightarrow 1.02$$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.44

44

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO**, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026


TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.45

45

SCHEDULERS

- FIFO: first in, first out
 - Very simple, easy to implement
- Consider
 - 3 x 10sec jobs, arrival: A B C, duration 10 sec each



Average turnaround time = $\frac{10 + 20 + 30}{3} = 20 \text{ sec}$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.46

46

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, **SJF**, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026


TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.47

47

SJF: SHORTEST JOB FIRST

- Given that we know execution times in advance:
 - Run in order of duration, shortest to longest
 - Non preemptive scheduler
 - This is not realistic
- Arrival: A B C, duration a=100 sec, b/c=10sec



Average turnaround time = $\frac{10 + 20 + 120}{3} = 50 \text{ sec}$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.48

48

SJF: WITH RANDOM ARRIVAL

- If jobs arrive at any time: duration a=100s, b/c=10s
- A @ t=0sec, B @ t=10sec, C @ t=10sec

Average turnaround time = $\frac{100 + (110 - 10) + (120 - 10)}{3} = 103.33 \text{ sec}$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.49

49

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.50

50

STCF: SHORTEST TIME TO COMPLETION FIRST

- Consider: duration a=100sec, b/c=10sec
- A_{len}=100 A_{arrival}=0
- B_{len}=10, B_{arrival}=10, C_{len}=10, C_{arrival}=10

Average turnaround time = $\frac{(120 - 0) + (20 - 10) + (30 - 10)}{3} = 50 \text{ sec}$

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.51

51

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.52

52

SCHEDULING METRICS - 3

- Scheduling Metric #3: Response Time
- Time from when job arrives until it starts execution

$T_{\text{response}} = T_{\text{firstrun}} - T_{\text{arrival}}$

- STCF, SJF, FIFO
 - can perform poorly with respect to response time

What scheduling algorithm(s) can help minimize response time?

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.53

53

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026


TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.54

54

★

RR: ROUND ROBIN



- Run each job awhile, then switch to another distributing the CPU evenly (fairly)
- Scheduling Quantum is called a time slice
- Time slice is a multiple of the time period.

RR is fair, but performs poorly on metrics such as turnaround time

Process	Burst Time
P1	12

Round Robin scheduling algorithm Gantt chart

P1	P2	P3	P4	P5	P1	P2	P4	P1
0	5	10	14	19	24	29	32	37


Scheduling Quantum = 5 seconds

January 22, 2026TCSS422: Operating Systems (Winter 2026)School of Engineering and Technology, University of Washington - TacomaLS 55

55

RR EXAMPLE

- ABC arrive at time=0, each run for 5 seconds



OVERHEAD not considered

$$T_{average\ response} = \frac{0 + 5 + 10}{3} = 5sec$$
$$T_{average\ response} = \frac{0 + 1 + 2}{3} = 1sec$$

RR with a time-slice of 1sec (Good for Response Time)

January 22, 2026TCSS422: Operating Systems (Winter 2026)School of Engineering and Technology, University of Washington - TacomaLS 56

56

ROUND ROBIN: TRADEOFFS

★

Short Time Slice

Long Time Slice

Fast Response Time

Slow Response Time

High overhead from context switching

Low overhead from context switching

Time slice impact:


- Turnaround time (for earlier example): $ts(1,2,3,4,5)=14,14,13,14,10$
- Fairness: round robin is always fair, $J=1$

January 22, 2026TCSS422: Operating Systems (Winter 2026)School of Engineering and Technology, University of Washington - TacomaLS 57

57

SCHEDULING WITH I/O

- STCF scheduler
 - A: CPU=50ms, I/O=40ms, 10ms intervals
 - B: CPU=50ms, I/O=0ms
 - Consider A as 10ms subjobs (CPU, then I/O)
- Without considering I/O:



CPU utilization= 100/140=71%


Poor Use of Resources

January 22, 2026TCSS422: Operating Systems (Winter 2026)School of Engineering and Technology, University of Washington - TacomaLS 58

58

SCHEDULING WITH I/O - 2

- When a job initiates an I/O request
 - A is blocked, waits for I/O to complete, frees CPU
 - STCF scheduler assigns B to CPU
- When I/O completes → raise interrupt
 - Unblock A, STCF goes back to executing A: (10ms sub-job)



Cpu utilization = 100/100=100%

Overlap Allows Better Use of Resources


January 22, 2026TCSS422: Operating Systems (Winter 2026)School of Engineering and Technology, University of Washington - TacomaLS 59

59

Activities

Visual settingsEdit

When poll is active respond at PollEV.com/westloyd Send westloyd to 22333



W

Which scheduler, thus far, best address fairness and average response time of jobs?

0

First In - First Out (FIFO)

Shortest Job First (SJF)

Shortest Time to Completion First (STCF)

Round Robin

SEE MORE

Current responses

60

QUESTION: SCHEDULING FAIRNESS

- Which scheduler, this far, best addresses fairness and average response time of jobs?
- First In – First Out (FIFO)
- Shortest Job First (SJF)
- Shortest Time to Completion First (STCF)
- Round Robin (RR)
- None of the Above
- All of the Above

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma


L5.61

61

SCHEDULING METRICS

- Consider Three jobs (A, B, C) that require: $time_A=400ms$, $time_B=100ms$, and $time_C=200ms$
- All jobs arrive at $time=0$ in the sequence of A B C.
- Draw a scheduling graph to help compute the average response time (ART) and average turnaround time (ATT) scheduling metrics for the FIFO scheduler.

Example:



January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.62

62

Activities

Moderate Visual settings Edit

When poll is active respond at PollEv.com/weslloyd Send weslloyd and your message to 22333

W

What is the Average Response Time of the FIFO scheduler?

0

Join by Web

PollEv.com/weslloyd


Join by Text

Send weslloyd and your message to 22333

Loading...

Join by QR code

Scan with your camera app



Current responses

63

When poll is active respond at PollEv.com/weslloyd Send weslloyd and your message to 22333

W

What is the Average Turnaround Time of the FIFO scheduler?

0

Join by Web

PollEv.com/weslloyd


Join by Text

Send weslloyd and your message to 22333

Loading...

Join by QR code

Scan with your camera app




Current responses

64

SCHEDULING METRICS

- Consider Three jobs (A, B, C) that require: $time_A=400ms$, $time_B=100ms$, and $time_C=200ms$
- All jobs arrive at $time=0$ in the sequence of A B C.
- Draw a scheduling graph to help compute the average response time (ART) and average turnaround time (ATT) scheduling metrics for the SJF scheduler.

Example:



January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.65

65

Activities

Moderate Visual settings Edit

When poll is active respond at PollEv.com/weslloyd Send weslloyd and your message to 22333

W

What is the Average Response Time of the Shortest Job First Scheduler?

0

Join by Web

PollEv.com/weslloyd


Join by Text

Send weslloyd and your message to 22333

Loading...


Join by QR code

Scan with your camera app




Current responses


66




67




68




69



70



71



72

MLFQ: LONG RUNNING JOB

Three-queue scheduler, time slice=10ms

Priority

Q2

Q1

Q0

0

50

100

150

200

Long-running Job Over Time (msec)

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.73

73

MLFQ: BATCH AND INTERACTIVE JOBS

$A_{arrival_time} = 0ms, A_{run_time} = 200ms,$

$B_{run_time} = 20ms, B_{arrival_time} = 100ms$

Priority

Q2

Q1

Q0

0

50

100

150

200

Scheduling multiple jobs (ms)

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.74

74

MLFQ: BATCH AND INTERACTIVE - 2

Continuous interactive job (B) with long running batch job (A)

Low response time is good for B

A continues to make progress

The MLFQ approach keeps interactive job(s) at the highest priority

Q2

Q1

Q0

0

50

100

150

200

A Mixed I/O-intensive and CPU-intensive Workload (msec)

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.75

75

OBJECTIVES – 1/22

Questions from 1/20

Assignment 0

C Tutorial - Pointers, Strings, Exec in C

Chapter 6: Limited Direct Execution

Chapter 7: Scheduling Introduction

Scheduling metrics

Turnaround time, Jain's Fairness Index, Response time

FIFO, SJF, STCF, RR schedulers

Chapter 8: Multi-level Feedback Queue

MLFQ Scheduler

Job Starvation

Gaming the Scheduler

Examples

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.76

76

MLFQ: ISSUES

Starvation

[High Priority] Q8 → A → B → C → D → E → F

Q7

Q6

Q5

Q4

Q3

Q2

[Low Priority] Q1 → G → H

CPU bound batch job(s)

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.77

77

RESPONDING TO BEHAVIOR CHANGE

Q2

Q1

Q0

0

50

100

150

200

Starvation

Without Priority Boost

A:

B:

C:

Priority Boost

Reset all jobs to topmost queue after some time interval S

January 22, 2026

TCCS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.78

78

Slides by Wes J. Lloyd

L5.13

RESPONDING TO BEHAVIOR CHANGE - 2

- With priority boost
 - Prevents starvation

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.79

79

KEY TO UNDERSTANDING MLFQ – PB

- Without priority boost:
 - Rule 1:** If Priority(A) > Priority(B), A runs (B doesn't).
 - Rule 2:** If Priority(A) = Priority(B), A & B run in RR.
 - KEY:** If time quantum of a higher queue is filled, then we don't run any jobs in lower priority queues!!!

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.80

80

STARVATION EXAMPLE

- Consider 3 queues:
 - Q2 – HIGH PRIORITY – Time Quantum 10ms
 - Q1 – MEDIUM PRIORITY – Time Quantum 20 ms
 - Q0 – LOW PRIORITY – Time Quantum 40 ms
- Job A: 200ms no I/O
- Job B: 5ms then I/O
- Job C: 5ms then I/O
- Q2 fills up, starves Q1 & Q0
- A makes no progress

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.81

81

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, RR schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.82

82

MLFQ: ISSUES - 2

- Gaming the scheduler
 - Issue I/O operation at 99% completion of the time slice
 - Keeps job priority fixed – never lowered
- Job behavioral change
 - CPU/batch process becomes an interactive process

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.83

83

PREVENTING GAMING

- Improved time accounting:
 - Track total job execution time in the queue
 - Each job receives a fixed time allotment
 - When allotment is exhausted, job priority is lowered

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

LS.84

84

MLFQ: TUNING

- Consider the tradeoffs:
 - How many queues?
 - What is a good time slice?
 - How often should we “Boost” priority of jobs?
 - What about different time slices to different queues?

Example) 10ms for the highest queue, 20ms for the middle, 40ms for the lowest

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.85

85

OBJECTIVES – 1/22

- Questions from 1/20
- Assignment 0
- C Tutorial - Pointers, Strings, Exec in C
- Chapter 6: Limited Direct Execution
- Chapter 7: Scheduling Introduction
 - Scheduling metrics
 - Turnaround time, Jain's Fairness Index, Response time
 - FIFO, SJF, STCF, **RR** schedulers
- Chapter 8: Multi-level Feedback Queue
 - MLFQ Scheduler
 - Job Starvation
 - Gaming the Scheduler
 - Examples**

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.86

86

PRACTICAL EXAMPLE

- Oracle Solaris MLFQ implementation
 - 60 Queues →
 - w/ slowly increasing time slice (high to low priority)
 - Provides sys admins with set of editable table(s)
 - Supports adjusting time slices, boost intervals, priority changes, etc.
- Advice
 - Provide OS with hints about the process
 - Nice command → Linux

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.87

87

MLFQ RULE SUMMARY

- The refined set of MLFQ rules:
 - Rule 1:** If Priority(A) > Priority(B), A runs (B doesn't).
 - Rule 2:** If Priority(A) = Priority(B), A & B run in RR.
 - Rule 3:** When a job enters the system, it is placed at the highest priority.
 - Rule 4:** Once a job uses up its time allotment at a given level (regardless of how many times it has given up the CPU), its priority is reduced(i.e., it moves down on queue).
 - Rule 5:** After some time period S, move all the jobs in the system to the topmost queue.

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.88

88

Jackson deploys a 3-level MLFQ scheduler. The time slice is 1 for high priority jobs, 2 for medium priority, and 4 for low priority. This MLFQ scheduler performs a Priority Boost every 6 timer units. When the priority boost fires, the current job is preempted, and the next scheduled job is run in round-robin order.

Job	Arrival Time	Job Length
A	T=0	4
B	T=0	16
C	T=0	8

(11 points) Show a scheduling graph for the MLFQ scheduler for the jobs above. Draw vertical lines for key events and be sure to label the X-axis times as in the example. Please draw clearly. An unreadable graph will loose points.

HIGH

MED

LOW

0

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.90

89

EXAMPLE


- Question:
 - Given a system with a quantum length of 10 ms in its highest queue, how often would you have to boost jobs back to the highest priority level to guarantee that a single long-running (and potentially starving) job gets at least 5% of the CPU?
- Some combination of n short jobs runs for a total of 10 ms per cycle without relinquishing the CPU
 - E.g. 2 jobs = 5 ms ea; 3 jobs = 3.33 ms ea, 10 jobs = 1 ms ea
 - n jobs always uses full time quantum (10 ms)
 - Batch jobs starts, runs for full quantum of 10ms
 - All other jobs run and context switch totaling the quantum per cycle
 - If 10ms is 5% of the CPU, when must the priority boost be ???
 - ANSWER → Priority boost should occur every 200ms**

January 22, 2026

TCSS422: Operating Systems (Winter 2026)
School of Engineering and Technology, University of Washington - Tacoma

L5.90

90



91