


Tutorial 5 – Introduction to Lambda II: Working with Files in S3 and CloudWatch Events

Disclaimer: Subject to updates as corrections are found
Version 0.10
Scoring: 20 pts maximum

The purpose of this tutorial is to introduce the use of the Amazon Simple Storage Service (S3) from AWS Lambda to support receiving, processing, and/or creating files. Additionally, this tutorial introduces combining multiple Lambdas into a single Java project. The tutorial also describes how to configure a CloudWatch event rule to trigger a Lambda function in response to an S3 Write Data event that is tracked by setting up a CloudTrail log “trail”.

Goals of this tutorial include:

1. Create a new CreateCSV Lambda function to write a file to S3.
2. Create a new ProcessCSV Lambda function to read a file from S3.
3. Package these two Lambda functions into a single Java project to produce a single, combined jar file. With a combined JAR provides it is possible to set up the “Switchboard” architecture by adding flow-control code. In Tutorial 4, it is possible to implement the encode and decode functions together using a single project.
4. Create a CloudWatch event rule to trigger the ProcessCSV Lambda function as a “target”. The event rule is triggered when a file is uploaded to an S3 bucket by the CreateCSV Lambda function. This event is provided by setting up a CloudTrail log trail to track S3 Write Data events. CloudWatch event triggers provide a means to implement **asynchronous application flow control** as shown in the figure:



For example, Lambda functions can be triggered in response to data being available in S3.

1. Create a new SAAF Lambda function template application

On your laptop, create a new directory for the project files and clone the git SAAF project to start:

```
git clone https://github.com/wlloyduw/SAAF.git
```

Refer to Tutorial #4 for information on “SAAF”.

Also refer to Tutorial #4 regarding selection of the Java version 21 for AWS Lambda.

2. CreateCSV Lambda Function

In the SAAF project, rename the HelloPOJO.java class to CreateCSV.java.

If using the Netbeans IDE, in the project, right click on the classname, and select “Refactor | Rename”. Rename the “HelloPOJO” class to “CreateCSV”.

IMPORTANT TIP USING NETBEANS: Java Import statements can be automatically added to your code by pressing **CONTROL – SHIFT – i** for **imports...** this saves from having to manually determine and add the import statements at the top of the class file.

If using the command line, rename the file and use a text editor to modify the class name inside CreateCSV.java to match “CreateCSV”.

```
cd {base directory where project was cloned}/SAAF/java_template/src/main/java/lambda
mv HelloPOJO.java CreateCSV.java
```


In the Request.java class in the same directory, add 4 input parameters for this Lambda function. Define getter and setters methods accordingly:

Property Name	Property Type
Bucketname	String
Filename	String
Row	Int
Col	Int

Start by adding the class variables:

```
private String bucketname;
private String filename;
private int row;
private int col;
```

Then, if using NetBeans, RIGHT-CLICK on the Request.java class name and select “Refactor”, then select “Encapsulate Fields”. Using the dialog box, select the 4 ‘Create Getter’ and ‘Create Setter’ boxes and press the ‘Refactor’ button. Netbeans will then automatically create getter and setter methods.



Or alternatively, as an example look at existing “getName” and “setName” methods that encapsulate “String name” in Request.java. Copy this pattern to create new getter and setter methods for the four new variables above. These fields will allow a user calling the service to specify required parameters to create a new CSV file. The file will be stored in the S3 Bucket described by “bucketname”. The filename is described by “filename”. The CSV file will consist of comma-separated random numbers (range 1 to 1000). Row and Col specify the number of total rows and columns in the CSV file.

In the CreateCSV class handleRequest() method, at the top, after ‘START FUNCTION IMPLEMENTATION’, load the Request class variables into local variables:

```
int row = request.getRow();
int col = request.getCol();
String bucketname = request.getBucketname();
String filename = request.getFilename();
```

Next, generate a random matrix of values, storing each row in a separate String. Generate the CSV file text as follows adding this code to the handleRequest() method:

```
int val = 0;
StringWriter sw = new StringWriter();
Random rand = new Random();

for (int i=0;i<row;i++)
    for (int j=0;j<col;j++)
    {
        val = rand.nextInt(1000);
        sw.append(Integer.toString(val));
        if ((j+1)!=col)
            sw.append(",");
        else
            sw.append("\n");
    }
```

You will need to add the Java import statements. In Netbeans, press Control-Shift-i. This adds the import: “import java.util.Random;”. The next step is to write Java code to generate the S3 bucket file.

Working with the S3 Java API requires adding the Java support library. In maven, the library can be added directly editing the pom.xml file. The pom.xml file is under the java_template directory.


The dependencies can *alternatively* be added through the Netbeans IDE, by RIGHT-clicking on dependencies, and select “Add Dependency”, and then in the Query box type “s3” or “aws-java-sdk-s3”.

NOTE: When first using netbeans, the central repository index must be built. **This could take several minutes.** When first downloading the data for repository searches, look for a notification in the IDE which you must accept, to grant permission to download the dependencies from the Central Repository. It will not be possible to search the repository from the Netbeans IDE until the data is downloaded and the indexes are built. If you cannot wait, then edit the pom.xml Maven project file directly as described below.

Once the index is built, in the GUI search for “aws-java-sdk-s3” and select the version, such as ~ “1.11.218”...


This automatically includes all Java jar libraries required to work with Amazon S3.

Two more dependencies are required. Select the newest non-beta version. Beta versions have a “b” in the name. Search for “**jaxb-api**”. Add “javax.xml:jaxb-api” and “javax.xml.bind”.



```
▶ a javax.xml:jaxb-api
▶ a javax.xml.bind:jaxb-api
```

Select the newest non-beta versions:



```
▼ a javax.xml:jaxb-api
  2.1 [pom] - central
▼ a javax.xml.bind:jaxb-api
  2.4.0-b180830.0359 [jar] - central
  2.4.0-b180725.0427 [jar] - central
  2.3.1 [jar] - central
```

Alternatively, if not using Netbeans, the dependencies can be added in the **pom.xml** file in between the tags “<dependencies> </dependencies>” directly as follows:

```
<dependency>
  <groupId>com.amazonaws</groupId>
  <artifactId>aws-java-sdk-s3</artifactId>
  <version>1.11.218</version>
</dependency>
<dependency>
  <groupId>javax.xml</groupId>
  <artifactId>jaxb-api</artifactId>
  <version>2.1</version>
  <type>pom</type>
</dependency>
<dependency>
  <groupId>javax.xml.bind</groupId>
  <artifactId>jaxb-api</artifactId>
  <version>2.3.1</version>
</dependency>
```

Editing the pom.xml file directly may not automatically download related dependencies. If an error occurs, try the IDE search.

Note that the version of these dependencies were just discovered using the Netbeans 23 IDE with Java 21. If deploying with another version of Java the values may be somewhat different.

Once S3 dependencies have been included in the project, capture the StringBuilder output as a Byte Array, and use this to create a new input stream. Then create metadata for describing the file to be written to S3 and create the new file on Amazon S3. Add the following code to the handleRequest() method following the generation of the CSV text:

```
byte[] bytes = sw.toString().getBytes(StandardCharsets.UTF_8);
InputStream is = new ByteArrayInputStream(bytes);
ObjectMetadata meta = new ObjectMetadata();
meta.setContentLength(bytes.length);
meta.setContentType("text/plain");

// Create new file on S3
AmazonS3 s3Client = AmazonS3ClientBuilder.standard().build();
s3Client.putObject(bucketname, filename, is, meta);
```

The JSON response object returned by the CreateCSV service populates the “value” attribute. (*just like the Hello function !*) For CreateCSV set the value to be a string that describes the CSV file which is created. Modify the response.setValue() to:

```
response.setValue("Bucket:" + bucketname + " filename:" + filename + " size:" +
bytes.length);
```

Once these changes are completed, compile the project.

2. Deploy CreateCSV Lambda Function

Next, using the AWS Management Console, create a new CreateCSV Lambda service. Refer to Tutorial #4 to review the procedure to create an AWS Lambda function.

Be sure to specify the function handler:

```
lambda.CreateCSV: :handleRequest
```

For Tutorial #5, choose only ***one*** method for invoking your Lambda functions: either via curl and the API Gateway (REST endpoints), or using the “aws lambda” CLI. ***It is not necessary to configure both methods.***

If choosing curl for function invocation, be sure to configure API Gateway URLs (POST) for your Lambdas. Refer to tutorial #4.

3. Prepare to call CreateCSV Lambda Function: Create S3 Bucket

Begin by copying and adapting the callservice.sh script from tutorial 4. This is in SAAF/java_template/test/callservice.sh. Copy this script to the tutorial 5 project and redefine the input JSON object as follows:

```
json={"row":50,"col":10,"bucketname":"test.bucket.462562f24.aaa","filename":"test.csv"}
```

Next, create an S3 bucket named “test.bucket.462562f24.aaa” on the AWS management console replacing “aaa” with your initials.

Navigate to the “S3” Simple Storage Service from the dropdown list of services, and then inside S3 select the button on the upper-right:

Create bucket

Create the bucket as follows:

S3 Bucket names must be globally unique within a naming partition. AWS currently has three partitions: **aws (Standard Regions), aws-cn (China Regions), and aws-us-gov (AWS GovCloud (US)).**

No other user anywhere can duplicate the same bucket name !!!

See more about bucket naming rules:

<https://docs.aws.amazon.com/AmazonS3/latest/userguide/bucketnamingrules.html>

For the bucket name use: **test.bucket.462562.f24.aaa**

Replace “aaa” with your initials.

If the name is still not unique, modify as needed until it is unique.

Revise the bucket name in the JSON object to match accordingly.


For remaining options accept the default values, and press the **Create bucket** button.

Next, it is necessary to configure permissions for your AWS Lambda functions to access your S3 bucket.

In the AWS Management Console, navigate to Lambda, and inspect your function’s execution role’s configured policies.

In Lambda, select the “Configuration” tab, followed by “Permissions” on the left.


Lambda provides a BLUE link to open your security role under Execution Role and Role Name:




Note this is your dynamically generated security role name. Click on this blue link to navigate to your role under the IAM Management Console to edit the role to grant Lambda permission to access your S3 bucket.

Without the helpful link, this role can also be found by going to the upper right-hand corner, selecting your name, and in the drop-down choosing "Security credentials". Then on the left-hand side go to "Roles", and then search for the Lambda function's security role name.


Once you're looking at the Role Summary, on the right, click the "Add Permissions" button and select "Attach policies":



Next, search for the name of the policy under **Other permissions policies**:
Type the name of the policy: "AmazonS3FullAccess" and press ENTER.
Next select the policy by clicking the checkbox on the LEFT:



Then press the button on the right to attach the policy:



The policy should then be added to the Role.

This grants your Lambda function the permission to work with S3.

Every Lambda function that will work with S3 will need this permission.

Fine grained security policies can be specified by creating an inline policy with the Role editor as-needed.

4. Test your CreateCSV Lambda Function

To reduce/change verbosity (the number of metrics returned from SAAF) feel free to replace the call to `inspector.inspectAllDeltas()`; with another option. See tutorial #4 – page 21 for a list of inspect methods.

Now, test your CreateCSV Lambda function.

You will need to update the bucketname in `callservice.sh` to match your new bucket.

Optionally, try creating different sizes of CSV files by increasing or decreasing the values for “row” and “col”. Please note, for creating large CSV files, it may be necessary to increase timeout values in the API-Gateway and/or Lambda as creating large CSVs is slow.

Now try calling your function using the `callservice.sh` script (*inspect all call removed*):

```
$ ./call_service.sh
Invoking Lambda function using API Gateway

real  0m15.775s
user  0m0.026s
sys   0m0.005s

JSON RESULT:
{
  "runtime": 14769,
  "startTime": 1698737511037,
  "endTime": 1698737525806,
  "lang": "java",
  "version": 0.5,
  "value": "Bucket:test.bucket.462562f24.aaa filename:test.csv size:1952"
}
```

Next, verify that the CSV file has been created in your S3 bucket.

First try this using the AWS CLI. Try out the following commands.

Adjust bucketnames as needed:


```
$ aws s3 ls test.bucket.462562f24.aaa
2023-10-31 00:32:05          1952 test.csv
$ aws s3 ls s3://test.bucket.462562f24.aaa
2023-10-31 00:32:05          1952 test.csv
$ aws s3 cp s3://test.bucket.462562f24.aaa/test.csv .
download: s3://test.bucket.462562f24.aaa/test.csv to ./test.csv
$ cat test.csv
161,576,98,78,253,237,970,223,632,850
80,993,715,174,636,874,11,220,434,506
878,943,971,847,993,137,351,586,625,475
...
```


Note that “s3://test.bucket.462562f24.aaa/test.csv” is considered a URI or a Uniform Resource Identifier which is analogous (similar to) a URL.

The “aws s3 ls” command doesn’t require “s3://”, while “aws s3 cp” does.


Next, using the S3 GUI, inspect your bucket and verify that the test.csv file exists.

From the list of buckets, click on your bucket name.



Then click on the filename ‘test.csv’.

It is possible to download the file here using the ‘Download’ button. Also the ‘Open’ button shows the data. The ‘Object URL’ link does not work without first allowing public access to your bucket, which is not recommended. Downloading data from S3 (Data Transfer OUT from Amazon S3 To Internet) costs \$.09 per GB. **It is expensive to download large files to your laptop, for example !** Data transfer within the same region is free and approximately \$.02 per GB between regions.




5. Create ProcessCSV Lambda Function

Next, make a copy of the “CreateCSV” class called “ProcessCSV”.

If you’re using Netbeans, right click on your class file “CreateCSV” and select “Refactor | Copy”. Or alternatively press “ALT-C”.

A refactor popup appears:



Rename the class to “ProcessCSV”.

If not using Netbeans, copy the “CreateCSV” source file and create a new class called “ProcessCSV”. Adapt the Lambda function to read a CSV file called “filename” from the S3 bucket called “bucketname”. Replace the code in the handleRquest() method.

Remove the old code for CreateCSV, and replace with new code for ProcessCSV.

Adapt the example code provided from the URL and in the box below to read a file from S3 line-by-line. URL: <https://blog.webnrsolutions.com/use-aws-lambda-function>

Here is the most relevant sample code for this activity:

```
AmazonS3 s3Client = AmazonS3ClientBuilder.standard().build();

//get object file using source bucket and srcKey name
S3Object s3Object = s3Client.getObject(new GetObjectRequest(srcBucket, srcKey));

//get content of the file
InputStream objectData = s3Object.getObjectContent();

//scanning data line by line
String text = "";
Scanner scanner = new Scanner(objectData);
while (scanner.hasNext()) {
    text += scanner.nextLine();
}
scanner.close();
```

For the s3Client.getObject() request, you’ll need to provide the **bucketname** (replace srcBucket) and **filename** (replace srcKey) in the S3Client.getObject() API call.

!!! ### !!! ### !!! ### !!! ### !!! ### !!!

IMPERATIVE WARNING

When copying CreateCSV to create the ProcessCSV Java class, it is IMPERATIVE that the PutObject() call to the Simple Storage Service (S3) be removed from ProcessCSV.

In the next step of the tutorial, an EventBridge rule is created to TRIGGER a call to ProcessCSV when a PutObject S3 Event occurs on the S3 Bucket.

****IF**** the ProcessCSV Lambda function GENERATES S3 PutObject events, this will produce a CIRCULAR TRIGGER, and this will generate millions of AWS Lambda calls.

This generates tremendous activity that exhausts cloud credits across the CloudTrail, CloudWatch, Lambda, and Simple Storage Service services.

****BE SURE TO DELETE**** THE PutObject() CALL WHEN COPYING
CREATE CSV TO MAKE THE NEW PROCESS CSV CLASS

IMPERATIVE WARNING

!!! ### !!! ### !!! ### !!! ### !!! ### !!!

The ProcessCSV Lambda function should add up all of the numbers read from the CreateCSV CSV file to calculate the **average value** and **total value** of all elements.

Read each line of the CSV file and parse each individual comma-separated value. Use the code above to help start your solution.

Add the total of all values using a Java “long” primitive variable:

```
long total;
```

Track the total number of elements processed using another variable.

```
long elements;
```

At the end, use a Java “double” primitive, to calculate the average value for all elements in the entire CSV file:

```
double avg;
```

Calculate the average by dividing the total by the elements and storing in avg.

Add a logging statement to print the average value to the AWS Lambda log:

```
LambdaLogger logger = context.getLogger();  
logger.log("ProcessCSV bucketname:" + bucketname + " filename:" + filename + "  
avg-element:" + avg + " total:" + total);
```

Finally, adjust the “value” property of the response object for the ProcessCSV function:

```
response.setValue("Bucket: " + bucketname + " filename:" + filename + "
processed.");
```

Note:

AWS Lambda functions automatically receive permission to write out the CloudWatch logs.

This permission is included in the **AWSLambdaBasicExecutionRole** policy that is automatically created when you create the Lambda function.

Policies for the role assigned to your function can be viewed in the AWS Management Console from AWS Lambda by navigating to your function and then selecting the “Configuration” tab, followed by “Permissions” on the left. Lambda provides a BLUE link to open your security role under Execution Role and Role Name.

Click this link to inspect security policies assigned to your function.

Next EXPAND the “AWSLambdaBasicExecutionRole...” to inspect the policy to be sure you have permission to write to the CloudWatch logs. Click on “CloudWatch Logs”. Click on “{} JSON”.

A JSON description of the policy appears. An “Edit policy” button allows the JSON to be changed. You should have the Cloud Watch permissions as defined with the following JSON:

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "logs:CreateLogGroup",
      "Resource": "arn:aws:logs:us-east-2:465394327572:*"
    },
    {
      "Effect": "Allow",
      "Action": [
        "logs:CreateLogStream",
        "logs:PutLogEvents"
      ],
      "Resource": [
        "arn:aws:logs:us-east-2:465394327572:log-group:/aws/lambda/createCsv_562:*"
      ]
    }
  ]
}
```

Alternatively, if permissions are missing, you could attach the **CloudWatchEventsFullAccess** policy to your Role. Refer to how we previously added the **AmazonS3FullAccess** policy. Adding this policy adds more permissions than needed and is less secure and is not recommended.

Now, compile the project.

This will create a JAR file with both Lambda functions.

Your Java JAR package contains two function handlers. This is the basis for implementing the switchboard pattern. A switchboard **could be** implemented by having an initial Handler process the JSON and redirect the function call inside the JAR based on the Request.java inputs.

CREATE A NEW Lambda function called “processCSV” using the jar file, and specify the new handler for ProcessCSV:

lambda.ProcessCSV:handleRequest

BE SURE to grant “processCSV” full S3 permissions by adding the ‘AmazonS3FullAccess’ policy as done for “createCSV”.


6. Automatically Trigger ProcessCSV when CreateCSV creates a file in S3

Next, we’ll create a CloudWatch Event rule to fire the ProcessCSV Lambda function to run whenever a specific file is placed into the S3 bucket.

In the AWS Management Console, search for the “**CloudTrail**” service. CloudTrail is considered a Management & Governance Tool:




Under the ‘Management & Governance’ Tool group, the service is called “**CloudTrail**”:



And then click the button:



The GUI will vary depending on whether you are shown the “Quick trail create” GUI or the full trail GUI. If you are shown the “Quick trail create” GUI, press the link for the FULL GUI:



Create a trail as follows:

Trail name: **s3_1**

Storage Location

**** Create a new independent bucket for logging ****

Select “Create new S3 bucket” (select radio button)

Trail log bucket and folder:


Can just use the automatically generated unique name that is provided, or provide your own name.

Log file SSE-KMS encryption: *uncheck this – this should be disabled*

Then scroll down and click the **NEXT** button.

On the “**Choose log events**” screen, first uncheck **Management events**.

Then select **ONLY** “Data events”.



In the Data events box, be sure the box says **Basic event selectors are enabled**.

If not click the **button** for “**Switch to basic event selectors**”.

Next set the “**Data event source**” to be “**S3**” .


Uncheck Read and Write for: “All current and future S3 buckets” !

All current and future S3 buckets Read Write

You don’t want to create an event trigger for ALL buckets !

The trigger should be just for the bucket you just created where CSV files (createCSV) are published.

Now fill in the “Individual bucket selection” to associate a CloudTrail with an S3 data event (e.g. *adding files to your bucket*).



If you forgot your bucket name, use the **Browse button** to find your bucket. If you remember the exact name, just type it in: test.bucket.462562f24.aaa

UNCHECK READ !!!

We only want to call a Lambda function when files are written to the bucket.

Then click the **NEXT** button.

Review the settings, and then create the trail:

An orange rectangular button with the text "Create trail" in white.

Next, navigate to the “**CloudWatch**” service, also a Management tool:

On the left-hand side, under ‘**Events**’, select “**Rules**”.

You should now be in the **Amazon EventBridge** GUI.

Click the “Create Rule” button:

An orange rectangular button with the text "Create rule" in white.

Then configure a rule as follows:

Name: Give your rule a name

Event bus: default

Rule with an event pattern *(selected by default)*

Then select the **Next** button.

Scroll down and configure the **Event pattern** as shown in the screen image:

Event pattern [info](#)

Event source
 AWS service or EventBridge partner as source

AWS service
 The name of the AWS service as the event source

Event type
 The type of events as the source of the matching pattern

All events that are delivered via CloudTrail have **AWS API Call via CloudTrail as the value for **detail-type**.** Events from API actions that start with the keywords List, Get, or Describe are not processed by EventBridge, with the exception of events from the following STS actions: GetFederationToken and GetSessionToken. Data events (for example, for Amazon S3 object level events, DynamoDB, and AWS Lambda) must have trails configured to receive those events. [Learn more](#).

Event pattern
 Event pattern, or filter to match the events

```

1 {
2   "source": ["aws.s3"],
3   "detail-type": ["AWS API Call via CloudTrail"],
4   "detail": {
5     "eventSource": ["s3.amazonaws.com"],
6     "eventName": ["PutObject"],
7     "requestParameters": {
8       "bucketName": ["test.bucket.462562f24.aaa"]
9     }
10  }
11 }
  
```

Event Type Specification 1

Any operation

Specific operation(s)

Specific operation(s)

Event Type Specification 2

Any bucket

Specific bucket(s) by name

Specific bucket(s) by name

For **Specific Operations** select **PutObject**. Be sure to specify the specific bucket name. The press the **'Next'** button.

For **Select target(s)**, select **'AWS service'** and for 'select a target' choose **'Lambda function'**. Provide the name of your Lambda function to call in response to the event. Here is should be **ProcessCSV** (or the name you have used for the function).

Under **Additional settings**,
 Under **Configure target input**, select **Constant (JSON text)**.

In the **Specify the constant in JSON** provide JSON to pass to the function in the large text box:

Provide JSON:

```
{ "bucketname": "test.bucket.462562f24.aaa", "filename": "test.csv" }
```

Then select **Next**.

It is not necessary to add any tags, so select **Next** again.

Before creating the event rule, you'll have an opportunity to review the configuration.

If everything looks correct press “**Create rule**”.

******* WARNING ABOUT CLOUDWATCH EVENTS RULES *******

Previously a student created an invalid rule where the Lambda function that wrote a file to S3, was also the Lambda that was called by the rule. This combination resulted in a circular Lambda call. Once invoked, AWS Lambda kept “putting an object” to S3 causing the trigger to fire and call the Lambda function again endlessly. This was only discovered in the monthly bill after several weeks of run time. This resulted in a large number of Lambda calls, and charges that had to be reimbursed due to the bug. Be careful when defining rules!

Now, run your `callservice.sh` script again to call `createCSV`.

When `createCSV` finishes, the creation of a file in your S3 bucket should automatically trigger the `processCSV` Lambda function to process the file. The `processCSV` results will be written to the CloudWatch log.

7. Submitting the tutorial

To submit the tutorial, submit the results of the **ProcessCSV log file**, when **calling CreateCSV** to generate a 50x10 CSV file (500 total elements, 50 rows by 10 columns). Each element should have a value selected randomly by the code provided above ranging from (1..1000). In the AWS Management Console, navigate to AWS Lambda.

Go to your “ProcessCSV” function.

Click the “**Monitor**” tab:

Select the “**View logs in CloudWatch**” button:



The log stream entry at the top of the list should contain the most recent output.

`ProcessCSV` should have been called when `CreateCSV` created the `test.csv` file in the bucket.

Select the top log stream entry from the list.

Be sure to include time stamps. If time stamps are missing, on the right select ‘**Display**’ and ‘**View in columns with details**’. Now, CAPTURE THE SCREEN:

Timestamp	Message
	No older events at this moment. Retry
2022-10-27T02:40:18.702-07:00	START RequestId: 2a56331b-d521-4ad6-ae62-2c68f8a64aca Version: \$LATEST
2022-10-27T02:40:30.050-07:00	ProcessCSV bucket=test.bucket.462-502.new_filename=test.csv
2022-10-27T02:40:30.152-07:00	END RequestId: 2a56331b-d521-4ad6-ae62-2c68f8a64aca
2022-10-27T02:40:30.152-07:00	REPORT RequestId: 2a56331b-d521-4ad6-ae62-2c68f8a64aca Duration: 11449.73 ms Billed Duration: 11450 ms Memory Size: 512 MB Max Memory Used: 147 MB Init Duration: 431.96 ms
	No newer events at this moment. Auto retry paused . Resume


```

        "requestParameters": {
            "bucketName": "test.bucket.462-562.f22.aaa",
            "Host": "s3.us-east-2.amazonaws.com",
            "key": "test.csv"
        },
        "responseElements": null,
        "additionalEventData": {
            "SignatureVersion": "SigV4",
            "CipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
            "bytesTransferredIn": 21.0,
            "SSEApplied": "Default_SSE_S3",
            "AuthenticationMethod": "AuthHeader",
            "x-amz-id-2":
"9XnnlCm35b+Wff8GyRCi37ZmZkM3dqePLF0EzLxx2Qqos4n2kxn1e9QVRMw2UFuDCpdbS5gHLfI=",
            "bytesTransferredOut": 0.0
        },
        "requestID": "HXZX1QDVH51RNBEH",
        "eventID": "73f7c855-36c3-4e1e-acb7-920e281e3835",
        "readOnly": false,
        "resources": [
            {
                "type": "AWS::S3::Object",
                "ARN": "arn:aws:s3:::test.bucket.462-562.f22.aaa/test.csv"
            }, {
                "accountId": "123456789012",
                "type": "AWS::S3::Bucket",
                "ARN": "arn:aws:s3:::test.bucket.462-562.f22.aaa"
            }
        ],
        "eventType": "AwsApiCall",
        "managementEvent": false,
        "recipientAccountId": "123456789012",
        "eventCategory": "Data",
        "tlsDetails": {
            "tlsVersion": "TLSv1.2",
            "cipherSuite": "ECDHE-RSA-AES128-GCM-SHA256",
            "clientProvidedHostHeader": "s3.us-east-2.amazonaws.com"
        }
    },
    "region": "us-east-2",
    "version": "0",
    "account": "123456789012"
}

```

The properties of interest are:

```

detail.requestParameters.bucketName
detail.requestParameters.key

```

The following source code demonstrates parsing the bucketName and filename and printing them to the log file. This code can be modified to suit your purposes:

```

public HashMap<String, Object> handleRequest(HashMap<String, Object> request, Context context) {
    //Collect initial data.
    Inspector inspector = new Inspector();
    inspector.inspectAll();

    //*****START FUNCTION IMPLEMENTATION*****

    Gson gson = new GsonBuilder().setPrettyPrinting().create();
    LambdaLogger logger = context.getLogger();
    logger.log ("bucketName=" + ((HashMap)(HashMap) request.get("detail")).get("requestParameters").get("bucketName"));
    logger.log ("filename=" + ((HashMap)(HashMap) request.get("detail")).get("requestParameters").get("key"));
}

```

The event is provided as a nested HashMap object in Java. Each layer of JSON is a HashMap. Accessing the bucket parameters involves using the **detail** HashMap to access the **requestParameters** HashMap to read the **bucketName** and **key** fields.

Customize the sample code as needed to create a customized event handler that does not use a hard coded bucketname and filename.