


MATERIAL / PACE


■ Please classify your perspective on material covered in today's class (45 respondents):
■ 1-mostly review, 5-equal new/review, 10-mostly new
■ Average - 6.35 (↑ - previous 6.30)


■ Please rate the pace of today's class:
■ 1-slow, 5-just right, 10-fast
■ Average - 5.47 (↓ - previous 5.62)


May 27, 2021


TCSS422: Computer Operating Systems [Spring 2021]
School of Engineering and Technology, University of Washington-Tacoma






















ASSIGNMENT 3: INTRODUCTION TO LINUX KERNEL MODULES Linux Kernel Modules are modules of code that are loaded and unloaded into the Linux kernel on demand They extend the functionality of the kernel without integrating new code into the kernel which requires recompilation of the full kernel (can be time consuming) Kernel modules can be dynamically loaded and removed without rebooting the system sudo Ismod - lists actively loaded kernel modules HOW MANY DO YOU HAVE? - (sudo Ismod | wc - I)


















For the 4GB computer example, how many bits are available for page status bits?

32 - 12 VPN bits = 20 status bits
32 - 24 VPN bits = 8 status bits
32 - 16 VPN bits = 16 status bits
32 - 12 VPN bits = 12 status bits
32 - 20 VPN bits = 12 status bits
None of the above



For the 4GB computer, how many page tables (for user processes) would fill the entire 4GB of memory?


4 GB / 16 KB = 65,536


4 GB / 64 MB = 256


4GB / 256 KB = 16,384


4GB / 4MB = 1,024


None of the above






























































































































```
ADDRESS TRANSLATION CODE


// 5-level Linux page table address lookup
//
// Inputs:
// mm_struct - process's memory map struct
// vpage - virtual page address

// Define page struct pointers
pgd_t *pgd;
p4d_t *p4d;
pud_t *pud;
pmd_t *pud;
pmd_t *put;
pte_t *pte;
struct page *page;

May 27, 2021 | TCSS422: Operating Systems [Spring 2021]
School of Engineering and Technology, University of Washington-Taxoma | 117.67
```







MULTI LEVEL PAGE TABLE EXAMPLE - 3 Assume each page directory entry (PDE) and page table entry (PTE) requires 4 bytes: • 6 bits for the Page Directory Index (PDI) • 6 bits for the Page Table Index (PTI) • 12 offset bits 8 status bits • (#8) How much total memory is required to index the HelloWorld.c program using a two-level page table when we only need to translate 4 total pages? ■ HINT: we need to allocate one Page Directory and one Page Table.. ■ HINT: how many entries are in the PD and PT TCSS422: Operating Systems [Spring 2021] School of Engineering and Technology, University of Washington - Tacoma May 27, 2021 L17.72

