


# **SURVEY QUESTIONS** Survey has two questions: Be sure to add your questions about the previous class to the second question 1st question: After today's class, comment on any new concepts that you learned about? Have been getting questions here... 2<sup>nd</sup> question: After today's class, what point(s) remain least clear to you? >> Please add questions HERE TCSS558: Applied Distributed Computing [Winter 2021]


Slides by Wes J. Lloyd L10.2

School of Engineering and Technology, University of Washington - Tacoma

L10.4

February 9, 2021





## FEEDBACK FROM 2/4

I am not sure if I completely understand the
 Thread-level parallelism (TLP) equation.

 It would helpful if you could show us an example of how to use it.

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.7

#### THREAD-LEVEL PARALLELISM

Metric – measures degree of parallelism realized by running system, by calculating average utilization:


$$TLP = \frac{\sum_{i=1}^{N} i \cdot c_i}{1 - c_0}$$


- C<sub>i</sub> fraction of time that i threads are executed simultaneously
- N maximum threads that can execute at any one time
- C<sub>0</sub> is the fraction of time that 0 threads are executed -CPU is idle...

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.8





# OBJECTIVES - 2/9

- Questions from 2/4
- Assignment 1: Key/Value Store
  - Java Maven project template files posted
- Midterm Thursday February 11
- Chapter 3: Processes
  - Chapter 3.3: Clients
  - Chapter 3.4: Servers
- Midterm Thursday February 11
  - 2<sup>nd</sup> hour Tuesday February 9 practice midterm questions

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.11

#### **ASSIGNMENT 1**

- An extension of ~3-5 days is likely and will be posted
- Sunday TCP/UDP/RMI Key Value Store
- Implement a "GenericNode" project which assumes the role of a client or server for a Key/Value Store
- Recommended in Java (11 or 8)
- Client node program interacts with server node to put, get, delete, or list items in a key/value store

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.12

# OBJECTIVES - 2/9

- Questions from 2/4
- Assignment 1: Key/Value Store
  - Java Maven project template files posted
- Midterm Thursday February 11
- Chapter 3: Processes
  - Chapter 3.3: Clients
  - Chapter 3.4: Servers
- Midterm Thursday February 11
  - 2<sup>nd</sup> hour Tuesday February 9 practice midterm questions

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.13

# OBJECTIVES - 2/9


- Questions from 2/4
- Assignment 1: Key/Value Store
  - Java Maven project template files posted
- Midterm Thursday February 11
- Chapter 3: Processes
  - Chapter 3.3: Clients
  - Chapter 3.4: Servers
- Midterm Thursday February 11
  - 2<sup>nd</sup> hour Tuesday February 9 practice midterm questions


February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.14







#### X WINDOWS


- Layered architecture to transport UI over network
- Remote desktop functionality for Linux/Unix systems
- X kernel acts as a server
  - Provides the X protocol: application level protocol
  - Xlib instances (client applications) exchange data and events with X kernels (servers)
  - Clients and servers on single machine → Linux GUI
  - Client and server communication transported over the network → remote Linux GUI


February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.18

February 9, 2021





#### **EXAMPLE: VNC SERVER**

- How to Install VNC server on Ubuntu EC2 instance VM:
- sudo apt-get update
- # ubuntu 16.04
- sudo apt-get install ubuntu-desktop
- sudo apt-get install gnome-panel gnome-settingsdaemon metacity nautilus gnome-terminal
- # on ubuntu 18.04
- sudo apt install xfce4 xfce4-goodies
- sudo apt-get install tightvncserver # both
- Start VNC server to create initial config file
- vncserver :1

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.21

#### **EXAMPLE: VNC SERVER - UBUNTU 16.04**

- On the VM: edit config file: nano ~/.vnc/xstartup
- Replace contents as below (Ubuntu 16.04):

```
#!/bin/sh
export XKL_XMODMAP_DISABLE=1
unset SESSION_MANAGER
unset DBUS_SESSION_BUS_ADDRESS

[ -x /etc/vnc/xstartup ] && exec /etc/vnc/xstartup
[ -r $HOME/.Xresources ] && xrdb $HOME/.Xresources
xsetroot -solid grey

vncconfig -iconic &
gnome-panel &
gnome-settings-daemon &
metacity &
nautilus &
gnome-terminal &
```

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.22

#### **EXAMPLE: VNC SERVER - UBUNTU 18.04**

- On the VM:
- Edit config file: nano ~/.vnc/xstartup
- Replace contents as below (Ubuntu 18.04):

```
#!/bin/bash
xrdb $HOME/.Xresources
startxfce4 &
```


February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma


L10.23


#### VNC SERVER - UBUNTU 20.04 - GNOME

```
# install vnc server
sudo apt install tigervnc-standalone-server
Sudo apt install ubuntu-gnome-desktop
vncserver :1
                            # creates a config file
                            # stop server
vncserver -kill :1
vi ~/.vnc/xstartup
                            # edit config file
#!/bin/sh
# Start Gnome 3 Desktop
[ -x /etc/vnc/xstartup ] && exec /etc/vnc/xstartup
[ -r $HOME/.Xresources ] && xrdb $HOME/.Xresources
vncconfig -iconic &
dbus-launch --exit-with-session gnome-session &
sudo systemctl start gdm
                                   # start gnome desktop
sudo systemctl enable gdm
vncserver :1
                                   # restart vnc server
                TCSS558: Applied Distributed Computing [Winter 2021]
  February 9, 2021
                                                            L10.24
                School of Engineering and Technology, University of Washington - Tacoma
```



# EXAMPLE: VNC CLIENT On the client (e.g. laptop): Create SSH connection to securely forward port 5901 on the EC2 instance to your localhost port 5901 This way your VNC client doesn't need an SSH key ssh -i <ssh-keyfile> -L 5901:127.0.0.1:5901 -N -f -1 <username> <EC2-instance ip\_address> For example: ssh -i mykey.pem -L 5901:127.0.0.1:5901 -N -f -1 ubuntu 52.111.202.44





#### THIN CLIENTS

- Thin clients
  - X windows protocol
  - A variety of other remote desktop protocols exist:

Remote desktop protocols include the following:

- Apple Remote Desktop Protocol (ARD) Original protocol for Apple Remote Desktop on macOS machines.
- Appliance Link Protocol (ALP) a Sun Microsystems-specific protocol featuring audio (play and record), remote printing, remote USB, accelerated video
- . HP Remote Graphics Software (RGS) a proprietary protocol designed by Hewlett-Packard specifically for high end workstation remoting and collaboration.
- . Independent Computing Architecture (ICA) a proprietary protocol designed by Citrix Systems
- NX technology (NoMachine NX) Cross platform protocol featuring audio, video, remote printing, remote USB, H264-enabled.
- PC-over-IP (PCoIP) a proprietary protocol used by VMware (licensed from Teradici)<sup>[2]</sup>
- · Remote Desktop Protocol (RDP) a Windows-specific protocol featuring audio and remote printing
- Remote Frame Buffer Protocol (RFB) A framebuffer level cross-platform protocol that VNC is based on.
- SPICE (Simple Protocol for Independent Computing Environments) remote-display system built for virtual environments by Qumranet, now Red Hat
- Splashtop a high performance remote desktop protocol developed by Splashtop, fully optimized for hardware (H.264) including Intel / AMD chipsets, NVIDIA
  of media codecs, Splashtop can deliver high frame rates with low latency, and also low power consumption.
- . X Window System (X11) a well-established cross-platform protocol mainly used for displaying local applications; X11 is network transparent

February 9, 2021 TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

#### **THIN CLIENTS - 2**

- Applications should separate application logic from UI
- When application logic and UI interaction are tightly coupled many requests get sent to X kernel
- Client must wait for response
- Synchronous behavior and app-to-UI coupling adverselt affects performance of WAN / Internet
- Protocol optimizations: reduce bandwidth by shrinking size of X protocol messages
- Send only differences between messages with same identifier
- Optimizations enable connections with 9600 kbps

 February 9, 2021
 TCSS558: Applied Distributed Computing [Winter 2021]

 School of Engineering and Technology, University of Washington - Tacoma

#### THIN CLIENTS - 3

- Virtual network computing (VNC)
- Send display over the network at the pixel level (instead of X lib events)
- Reduce pixel encodings to save bandwidth fewer colors
- Pixel-based approaches loose application semantics
- Can transport any GUI this way
- THINC- hybrid approach
- Send video device driver commands over network
- More powerful than pixel based operations
- Less powerful compared to protocols such as X


February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.31

L10.32


# TRADEOFFS: ABSTRACTION OF REMOTE **DISPLAY PROTOCOLS** Tradeoff space: abstraction level of remote display protocols




February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]

School of Engineering and Technology, University of Washington - Tacoma





# CLIENT ROLES IN PROVIDING DISTRIBUTION TRANSPARENCY - 2

- Location/relocation/migration transparency
  - Harness convenient naming system to allow client to infer new locations
  - Server inform client of moves / Client reconnects to new endpoint
  - Client hides network address of server, and reconnects as needed
  - May involve temporary loss in performance
- Replication transparency
  - Client aggregates responses from multiple servers
- Failure transparency
  - Client retries, or maps to another server, or uses cached data
- Concurrency transparency
  - Transaction servers abstract coordination of multithreading

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.35

WE WILL RETURN AT 2:55PM


# OBJECTIVES - 2/9

- Questions from 2/4
- Assignment 1: Key/Value Store
  - Java Maven project template files posted
- Midterm Thursday February 11
- Chapter 3: Processes
  - Chapter 3.3: Clients
  - Chapter 3.4: Servers
- Midterm Thursday February 11
  - 2<sup>nd</sup> hour Tuesday February 9 practice midterm questions

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.37



#### **SERVERS**

- Cloud & Distributed Systems rely on Linux
- http://www.zdnet.com/article/it-runs-on-the-cloud-and-thecloud-runs-on-linux-any-questions/
- IT is moving to the cloud. And, what powers the cloud?
  - Linux
- Uptime Institute survey 1,000 IT executives (2016)
  - 50% of IT executives plan to migrate majority of IT workloads to off-premise to cloud or colocation sites
  - 23% expect the shift in 2017, 70% by 2020...
- Docker on Windows / Mac OS X
  - Based on Linux
  - Mac: Hyperkit Linux VM
  - Windows: Hyper-V Linux VM

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.39

#### SERVERS - 2

- Servers implement a specific service for a collection of clients
- Servers wait for incoming requests, and respond accordingly
- Server types
- Iterative: immediately handle client requests
- Concurrent: Pass client request to separate thread
- Multithreaded servers are concurrent servers
  - E.g. Apache Tomcat
- Alternative: fork a new process for each incoming request
- <u>Hybrid</u>: mix the use of multiple processes with thread pools

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.40


#### **END POINTS**

- Clients connect to servers via:
  IP Address and Port Number
- How do ports get assigned?
  - Many protocols support "default" port numbers
  - Client must find IP address(es) of servers
  - A single server often hosts multiple end points (servers/services)
  - When designing new TCP client/servers must be careful not to repurpose ports already commonly used by others

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.41



#### **TYPES OF SERVERS**

- Daemon server
  - Example: NTP server
- Superserver
- Stateless server
  - Example: Apache server
- Stateful server
- Object servers
- EJB servers

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.43

#### NTP EXAMPLE

- Daemon servers
  - Run locally on Linux
  - Track current server end points (outside servers)
  - Example: network time protocol (ntp) daemon
    - Listen locally on specific port (ntp is 123)
    - Daemons routes local client traffic to the configured endpoint servers
    - University of Washington: time.u.washington.edu
    - Example "ntpq -p"
      - Queries local ntp daemon, routes traffic to configured server(s)

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.44

#### **SUPERSERVER**

- Linux inetd / xinetd
  - Single superserver
  - Extended internet service daemon
  - Not installed by default on Ubuntu
  - Intended for use on server machines
  - Used to configure box as a server for multiple internet services
    - E.g. ftp, pop, telnet
  - inetd daemon responds to multiple endpoints for multiple services
  - Requests fork a process to run required executable program
- Check what ports you're listening on:
  - sudo netstat -tap | grep LISTEN

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.45

#### INTERRUPTING A SERVER

- Server design issue:
  - Active client/server communication is taking place over a port
  - How can the server / data transfer protocol support interruption?
- Consider transferring a 1 GB image, how do you pass a unrelated message in this stream?
  - 1. <u>Out-of-band</u> data: special messages sent in-stream to support interrupting the server (*TCP urgent data*)
  - 2. Use a separate connection (different port) for admin control info
- Example: sftp secure file transfer protocol
  - Once a file transfer is started, can't be stopped easily
  - Must kill the client and/or server

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.46

#### **STATELESS SERVERS**

- Data about state of clients is not stored
- Example: web application servers are typically stateless
  - Also function-as-a-service (FaaS) platforms
- Many servers maintain information on clients (e.g. log files)
- Loss of stateless data doesn't disrupt server availability
  - Loosing log files typically has minimal consequences
- Soft state: server maintains state on the client for a limited time (to support sessions)
- Soft state information expires and is deleted

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.47

#### STATEFUL SERVERS

- Maintain persistent information about clients
- Information must be explicitly deleted by the server
- Example:

File server - allows clients to keep local file copies for RW

- Server tracks client file permissions and most recent versions
  - Table of (client, file) entries
- If server crashes data must be recovered
- Entire state before a crash must be restored
- Fault tolerance Ch. 8

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.48

#### **STATEFUL SERVERS - 2**

- Session state
  - Tracks series of operations by a single user
  - Maintained temporarily, not indefinitely
  - Often retained for multi-tier client server applications
  - Minimal consequence if session state is lost
  - Clients must start over, reinitialize sessions
- Permanent state
  - Customer information, software keys
- Client-side cookies
  - When servers don't maintain client state, clients can store state locally in "cookies"
  - Cookies are not executable, simply client-side data

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.49

#### **OBJECT SERVERS**

- OBJECTIVE: Host objects and enable remote client access
- Do not provide a specific service
  - Do nothing if there are no objects to host
- Support adding/removing hosted objects
- Provide a home where objects live
- Objects, themselves, provide "services"
- Object parts
  - State data
  - Code (methods, etc.)
- Transient object(s)
  - Objects with limited lifetime (< server)</li>
  - Created at first invocation, destroyed when no longer used (i.e. no clients remain "bound").
  - Disadvantage: initialization may be expensive
  - Alternative: preinitialize and retain objects on server start-up

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.50

#### **OBJECT SERVERS - 2**

- Should object servers isolate memory for object instances?
  - Share neither code nor data
  - May be necessary if objects couple data and implementation
- Object server threading designs:
  - Single thread of control for object server
  - One thread for each object
  - Servers use separate thread for client requests
- Threads created on demand vs.

Server maintains pool of threads

What are the tradeoffs for creating server threads on demand vs. using a thread pool?

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.51


#### **EJB - ENTERPRISE JAVA BEANS**


- EJB- specialized Java object hosted by a EJB web container
- 4 types: stateless, stateful, entity, and message-driven beans
- Provides "middleware" standard (framework) for implementing back-ends of enterprise applications
- EJB web application containers integrate support for:
  - Transaction processing
  - Persistence
  - Concurrency
  - Event-driven programming
  - Asynchronous method invocation
  - Job scheduling
  - Naming and discovery services (JNDI)
  - Interprocess communication
  - Security
  - Software component deployment to an application server

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.52





#### LAN REQUEST DISPATCHING

- Front end of three tier architecture (logical switch) provides distribution transparency – hides multiple servers
- Transport-layer switches: switch accepts TCP connection requests, hands off to a server
  - Example: hardware load balancer (F5 networks Seattle)
  - HW Load balancer OSI layers 4-7
- Network-address-translation (NAT) approach:
  - All requests pass through switch
  - Switch sits in the middle of the client/server TCP connection
  - Maps (rewrites) source and destination addresses
- Connection hand-off approach:
  - TCP Handoff: switch hands of connection to a selected server

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.55

# LAN REQUEST DISPATCHING - 2

Logically a single TCP connection

Request

- Who is the best server to handle the request?
- Switch plays important role in distributing requests
- Implements load balancing
- Round-robin routes client requests to servers in a looping fashion
- Transport-level route client requests based on TCP port number
- Content-aware request distribution route requests based on inspecting data payload and determining which server node should process the request

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.56

Server

Server

Request

(handed off)

Response

#### **WIDE AREA CLUSTERS**

- Deployed across the internet
- Leverage resource/infrastructure from Internet Service Providers (ISPs)
- Cloud computing simplifies building WAN clusters
- Resource from a single cloud provider can be combined to form a cluster
- For deploying a cloud-based cluster (WAN), what are the implications of deploying nodes to:
- (1) a single availability zone (e.g. us-east-1e)?
- (2) across multiple availability zones?

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.57

#### WAN REQUEST DISPATCHING

- Goal: minimize network latency using WANs (e.g. Internet)
- Send requests to nearby servers
- Request dispatcher: routes requests to nearby server
- Example: Domain Name System
  - Hierarchical decentralized naming system
- Linux: find your DNS servers:
  - # Find you device name of interest nmcli dev
  - # Show device configuration
    nmcli device show <device name>

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.58


#### **DNS LOOKUP**

- First query local server(s) for address
- Typically there are (2) local DNS servers
  - One is backup
- Hostname may be cached at local DNS server
  - E.g. www.google.com
- If not found, local DNS server routes to other servers
- Routing based on components of the hostname
- DNS servers down the chain mask the client IP, and use the originating DNS server IP to identify a local host
- Weakness: client may be far from DNS server used. Resolved hostname is close to DNS server, but not necessarily close to the client

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.59



#### **DNS: LINUX COMMANDS**

- nslookup <ip addr / hostname>
- Name server lookup translates hostname or IP to the inverse
- traceroute <ip addr / hostname>
- Traces network path to destination
- By default, output is limited to 30 hops, can be increased

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.61

#### DNS EXAMPLE - WAN DISPATCHING

- Ping <u>www.google.com</u> in WA from wireless network:
  - nslookup: 6 alternate addresses returned, choose (74.125.28.147)
  - Ping 74.125.28.147: Average RTT = 22.458 ms (11 attempts, 22 hops)
- Ping <u>www.google.com</u> in VA (us-east-1) from EC2 instance:
  - nslookup: 1 address returned, choose 172.217.9.196
  - Ping 172.217.9.196: Average RTT = 1.278 ms (11 attempts, 13 hops)
- From VA EC2 instance, ping WA www.google server
- Ping 74.125.28.147: Average RTT 62.349ms (11 attempts, 27 hops)
- Pinging the WA-local server is ~60x slower from VA
- From local wireless network, ping VA us-east-1 google :
- Ping 172.217.9.196: Average RTT=81.637ms (11 attempts, 15 hops)

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.62

## DNS EXAMPLE - WAN DISPATCHING

- Ping www.google.com in WA from wireless network:
  - nslookup: 6 alternate addresses returned, choose (74.125.28.147)

#### Latency to ping VA server in WA: ~3.63x

WA client: local-google 22.458ms to VA-google 81.637ms

#### Latency to ping WA server in VA: ~48.7x

VA client: local-google 1.278ms to WA-google 62.349!

- From local wireless network, ping VA us-east-1 google:
- Ping 172.217.9.196: Average RTT=81.637ms (11 attempts, 15 hops)

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington - Tacoma

L10.63

#### **OBJECTIVES - 2/9**

- Questions from 2/4
- Assignment 1: Key/Value Store
  - Java Maven project template files posted
- Midterm Thursday February 11
- Chapter 3: Processes
  - Chapter 3.3: Clients
  - Chapter 3.4: Servers
- Midterm Thursday February 11
  - 2<sup>nd</sup> hour Tuesday February 9 practice midterm questions

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.64

#### **PRACTICE MIDTERM**

- Envisioned as a class activity
- Form groups using Zoom breakout rooms
- Each group works on 2 assigned questions
- Group submits PDF solution by end of day today
  - Late submission accepted through 5pm Wednesday
- Instructor shares best solutions provided from the class submission via Canvas by Wednesday morning
  - Subject to updates for late submissions
- All students have access to solutions for review and practice
- Follow link:

https://bit.ly/3p8aLzH

February 9, 2021

TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma

L10.65

