



TCSS 558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, UW-Tacoma










MATERIAL / PACE

■ Please classify your perspective on material covered in today's class (22 respondents):
■ 1-mostly review, 5-equal new/review, 10-mostly new
■ Average - 6.41 (↑ - previous 5.80)

■ Please rate the pace of today's class:
■ 1-slow, 5-just right, 10-fast
■ Average - 5.86 (↑ - previous 5.27)

TCSSSS: Applied Distributed Computing [Winter 2021]
School of Engineering and Technology, University of Washington-Tacoma



TCSS 558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, UW-Tacoma

OBJECTIVES - 2/23

Questions from 2/18

Assignment 0


Assignment 2: Replicated Key Value Store

Chapter 4: Communication

Chapter 4.1: Foundations

Chapter 4.2: RPC (light-review)


Chapter 4.3: Message Oriented Communication





February 23, 2021

OBJECTIVES - 2/23

Questions from 2/18
Assignment 0
Assignment 2: Replicated Key Value Store
Chapter 4: Communication
Chapter 4.1: Foundations
Chapter 4.2: RPC (light-review)
Chapter 4.3: Message Oriented Communication









1. PRECOPY: Push all memory pages to new machine (slow), resend modified pages later, transfer control 2. STOP-AND-COPY: Stop the VM, migrate memory pages, start new VM 3. ON DEMAND: Start new VM, copy memory pages as needed 4. HYBRID: PRECOPY and followed by brief STOP-AND-COPY What are some advantages and disadvantages of 1-4? (+) 1/3: no loss of service (+) 4: fast transfer, minimal loss of service (+) 2: fastest data transfer (+) 3: new VM immediately available (-) 1: must track modified pages during full page copy (-) 2: longest downtime - unacceptable for live services (-) 3: prolonged, slow, migration (-) 3: original VM must stay online for quite a while (-) 1/3: network load while original VM still in service L13.13
































































TYPES OF COMMUNICATION ■ Persistent communication Message submitted for transmission is stored by communication middleware as long as it takes to deliver it Example: email system (SMTP) Receiver can be offline when message sent Temporal decoupling (delayed message delivery) Transient communication Message stored by middleware only as long as sender/receiver applications are running If recipient is not active, message is dropped Transport level protocols typically are transient (no msg storage) What OSI protocol level is the SMTP Protocol? TCSS58: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma February 23, 2021 L13.35














































































































































AMQP PROTOCOL Message-queueing systems initially developed to enable legacy applications to interoperate Decouple inter-application communication to "open" messaging-middleware Many are proprietary solutions, so not very open e.g. Microsoft Message Queueing service, Windows NT 1997 Advanced message queueing protocol (AMQP), 2006 Address openness/interoperability of proprietary solutions Open wire protocol for messaging with powerful routing capabilities Help abstract messaging and application interoperability by means of a generic open protocol Suffer from incompatibility among protocol versions ■ pre-1.0, 1.0+ TCSS558: Applied Distributed Computing [Winter 2021] School of Engineering and Technology, University of Washington - Tacoma February 23, 2021 L13.85

